

Eaton LPJ-6SP

Catalog Number: LPJ-6SP

Eaton Bussmann series LPJ fuse, Low-peak fuse, 6 A, Dual, Class J, Non-indicating, Ferrule end x ferrule end, Time delay/Current-limiting, 10 sec at 500%, 100 kAIC Vdc|300 kAIC at 600 V, Standard, 600 V, 300 Vdc

General specifications

| | |
|--------------------------------|----------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series LPJ fuse | LPJ-6SP |
| UPC | Product Length/Depth |
| 051712523264 | 2.25 in |
| Product Height | Product Width |
| .81 in | .81 in |
| Product Weight | Warranty |
| .19 lb | Not Applicable |
| Compliances | |
| CE Marked RoHS Compliant | |



Electrical rating

Amperage Rating

6 A

Interrupt rating

300 kAIC at 600 Vac

100 kAIC Vdc

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

Physical details

Fuse type

Time delay

Current-limiting

Number of elements

Dual

Packaging type

Standard

General information

Class

Class J

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Non-indicating, High in-rush current motor protection

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

LPJ-6SP-LOW-PEAK CLASS J T/D

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - LPJ-6SP

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)