

Eaton C10M16

Catalog Number: C10M16

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 16 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10M16
	UPC
	051712754606
EAN	Product Length/Depth
5027590493666	38 mm
Product Height	Product Width
10 mm	10 mm
Product Weight	Warranty
8.2 g	1 year limited
Compliances	Certifications
CE Marked GoST-R RoHS Compliant	IEC 60269



Product specifications

Fuse indicator

Other

Construction size

10 x 38 mm

10 mm x 38 mm

Rated voltage AC

500 V

Connection

Ferrule end x ferrule end

Quantity

10

Suitable for

CHM Modular fuse holder

Material

Ceramic

Release characteristic

Other

Amperage Rating

16 A

Frequency rating - max

62 Hz

Utilization category

aM (switchgear protection)

Watt losses

.92 W

Fuse type

C10M

Type

fuse

Fuse shape

Cylindrical

Breaking capacity

120 kA

Fuse size

10 x 38 mm

Resources

Catalogs

Product overview for machinery

Bussmann series complete full line catalog no. 1007

Compliance information

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Specifications and datasheets

Eaton Specification Sheet - C10M16

Technical data sheets

720115 Cylindrical fuses

Frequency rating - min

45 Hz

Class

Class aM

Voltage rating

500 V

Application

motor protection

for industrial applications

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)