Ordering, Electrical and Technical Data (Subject to change without notice)

Product Number	Model Number	Ordering Code	Description	Lamp Type	Base	Nom. Watts	Rated Life [1]	Approx. Lumens [2]	CRI	Color Temp (K)
Standard Incandescent A19 60W Equivalent										
45809-1	9290011750	9.5A19/LED/827 ND 120V	60W Non-Dim	A19	E26	9.5	10,950	800	>80	2700
45560-0	9290011352	8A19/LED/850 ND 120V	60W Non-Dim	A19	E26	8	10,950	800	>80	5000
Standard Incandescent A19 100W Equivalent										
45568-3	9290011349	14.5A19/LED/827 ND 120V	100W Non-Dim	A19	E26	14.5	10,950	1500	>80	2700
45571-7	9290011351	14A19/LED/850 ND 120V	100W Non-Dim	A19	E26	14	10,950	1500	>80	5000
Standard Incandescent BR30 65W Dimmable Equivalent										
45810-9	9290011749	9BR30/LED/827/DIM 120V	65W Dim	BR30	E26	9	10,950	650	>80	2700
Standard Incandescent PAR38 90W Equivalent										
45799-3	9290011747	11PAR38/F25/830 ND 120V	90W Non-Dim	PAR38	E26	11	10,950	950	>80	3000

1. Rated average life based on engineering testing and probability analysis.
2. Based on photometric testing consistent with IES LM-79.

Footnotes from front:

* When compared to a 1000 hour A19 incandescent, the 10,950 hour LED A19 lamp has more than 10 times the life.

** The 8W and 9.5W LED A19 lamps produce 800 lumens as compared to the 800 lumens produced by a 60W incandescent. The 14W and 14.5W LED A19 lamps produce 1500 lumens as compared to the 1600 lumens produced by a 100W incandescent. The 9W LED BR30 produces 650 lumens as compared to the 650 lumens produced by a 65W incandescent. The 11W LED PAR38 produces 4085 cd (candela) as compared to the 3698 cd produced by a 90W halogen.

Shipping Data (Subject to change without notice)

Product Number	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs.)	Case Cube (cu. Ft.)	Pallet Qty	SKUs per Layer	Layers High	SKU Dimensions (W x D x H) (In.)	Case Dimensions (W x D x H) (In.)	Pallet Dimensions (W x D x H) (In.)
Standard Incandescent A19 60W Equivalent											
45809-1	45809-6	45809-1	6	3.84	0.124	1764	252	7	2.5 x 2.5 x 4.4	7.8 x 5.4 x 5.1	47.2 x 39.4 x 41.5
45560-0	45560-6	45560-1	6	3.84	0.124	1764	252	7	2.5 x 2.5 x 4.4	7.8 x 5.4 x 5.1	47.2 x 39.4 x 41.5
Standard Incandescent A19 100W Equivalent											
45568-3	45568-2	45568-7	6	3.84	0.124	1764	252	7	2.5 x 2.5 x 4.4	7.8 x 5.4 x 5.1	47.2 x 39.4 x 41.5
45571-7	45571-2	45571-7	6	3.84	0.124	1764	252	7	2.5 x 2.5 x 4.4	7.8 x 5.4 x 5.1	47.2 x 39.4 x 41.5
Standard Incandescent BR30 65W Dimmable Equivalent											
45810-9	45810-2	45810-7	6	2.99	0.423	450	90	5	4.1 x 4.1 x 5.7	13 x 8.8 x 6.4	47.2 x 39.4 x 37.8
Standard Incandescent PAR38 90W Equivalent											
45799-3	45799-0	45799-5	6	10.6	0.641	270	54	5	5.2 x 5.2 x 5.8	15.9 x 10.8 x 6.4	47.2 x 39.4 x 38

RoHS COMPLIANT

c UL us LISTED

' 2015 Koninklijke Philips N.V. All rights reserved.
Philips reserves the right to make changes in speci cations and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

PLt-1580BN 08/15 philips.com

Philips Lighting North America Corporation
200 Franklin Square Drive, Somerset, NJ 08873
Tel. 855-486-2216

Philips Lighting Canada Ltd.
281 Hillmount Rd, Markham, ON, Canada L6C 2S3
Tel. 800-668-9008