

474 Series 240 Volt Dual Heat Fan Forced Portable Heater

82



- 1920W & 3840W heat settings
- Temperature control thermostat
- Manual reset type limit control
- 6' long - 3 conductor cord
- Imported to TPI Corporation
V S H F L ζ F D W L R Q V

Width: 16"
Height: 16"
Depth: 8¹/₂"



20 AMP Plug
NEMA #6-20P


MFG CATALOG NUMBER	MFG MODEL NUMBER	WATTS	MAX BTUs	VOLTS	AMPS	PHASE	WT. (LBS)
04461802	H474TM-C	1920/3840	13106	240	8.0 / 16.0	1	20

5800 Series Garage/Workshop 240/208 Volt Fan Forced Portable Heater



- Up to 4800 Watts of heating comfort for garage or utility room applications
- 4000 Watts available for smaller areas.
- Built in bi-metal double pole thermostat - 50° to 90° range.
- Steel tubular heating element
- Wall/Ceiling bracket included
- Manual reset standard
- Power on and overheat pilot lights
- Imported to TPI Corporation
V S H F L ζ F D W L R Q V

ITEM	WIDTH	HEIGHT	DEPTH
Heater	10.625	11"	9.625"
Bracket	2.5"	10"	14.0"



MFG CATALOG NUMBER	MFG MODEL NUMBER	WATTS	MAX BTUs	VOLTS	AMPS	PHASE	PLUG TYPE	WT. (LBS)
05034002	HF5840TC	4000/3000	13652	240 / 208	16.6 / 14.4	1	20 Amp	17
05033902	HF5848TC	4800/3600	15086		20 / 17.3		30 Amp	

ICH Series 240/208 Volt Construction Site/Utility Fan Forced Portable Heater

- Operates on 240V or 208V
- Steel tubular heating element
- 43°F air heat rise
- Internal overheat thermostat
- Temperature control thermostat
- 6' long cordset
- Imported to TPI Corporation
V S H F L ζ F D W L R Q V



20 AMP Plug
NEMA #6-20P

Width: 10⁵/₈"
Height: 12³/₈"
Depth: 10"



MFG CATALOG NUMBER	MFG MODEL NUMBER	WATTS	MAX BTUs	VOLTS	AMPS	PHASE	WT. (LBS)
04508702	ICH-240C	4000 / 3000	13648	240 / 208	16.7 / 14.4	1	15

680 Series "Bulldog" 240/208 Volt Fan Forced Portable Unit Heater

6 Z L Y H O E D V H D O O R Z V X Q L W W R
ceiling mounted.



- Operates on 240V or 208V
- Finned steel tubular heating element
- Internal manual reset thermal cut-out
- 6' long cord with molded plug
- Temperature control thermostat with 35°F to 85°F range
- 10' air throw - 262 CFM



20 AMP Plug
NEMA #6-20P
HF684TC



30 AMP Plug
NEMA #6-30P
HF685TC,
HF686TC

Width: 13¹/₈"
Height: 17¹/₈"
Depth: 11¹/₂"

‡ , P S R U W H G W R 7 3 , & R U S R U D W L R Q V S H F L ζ F D W L R Q V

MFG CATALOG NUMBER	MFG MODEL NUMBER	WATTS	MAX BTUs	VOLTS	PHASE	AMPS	TEMP RISE	WT. (LBS)
04462802	* HF684TC	4000/3000	13652/10239	240/208	1	16.7/14.5	48°F	20
04462902	HF685TC	4800/3600	16384/12288	240/208	1	20.0/17.4	58°F	20
04463002	HF686TC	5600/4200	19107/14330	240/208	1	23.4/20.2	75°F	20
06835002	A1560	OPTIONAL WALL CEILING BRACKET FOR HF680 & ICH 240C SERIES HEATERS						

* HF684TC UL listed only