



Hydraulic Punch Driver and Kits



7806SB



7906SB

The Quick Draw™ and the Quick Draw 90™ feature:

- Optional step-saver adapter converts standard Greenlee punches through 1-1/4" conduit size to use 7/16" (11.1 mm) draw stud (adapter and draw stud included with 7804SB only).
- Compact, lightweight design for portability and fast, easy one-person operation.
- Develops 8 tons of hydraulic force for easy punching, even in 10-gauge stainless steel depending on individual punch capacities.
- Quick Draw is perfect for fast, straight-on front panel punching.
- Quick Draw 90's right angle driver head rotates over 180 degrees for maximum flexibility in tight working areas.
- Can be used with non-round punches within the capacity of the tool (adapter may be required).

Cat. No.	UPC No.	Description	Weight	
			lbs.	kg.
7804SB	34292	Quick Draw™ Driver, 3 draw studs, 2 adapters, 1 spacer and case	10	4.5
7806SB	34293	Standard - Quick Draw™ Driver, 1/2" through 2" Slug Buster® conduit size punches and dies 2 draw studs, 1 adapter, 1 spacer and case	14	6.4
7804E	34291	Metric - Quick Draw™ Driver, 2 draw studs, 1 adapter, 1 spacer and case	9.4	4.3
7804ESB	35611	Metric - Quick Draw™ Driver, Slug-Buster® Pg punches and dies 15.2 mm through 30.5 mm, 2 draw studs, 1 adapter, 1 spacer and case	10.3	4.7
7804ISO	35614	Metric - Quick Draw™ Driver, Slug-Buster® ISO punches and dies 16.2 mm through 40.5 mm, 2 draw studs, 1 adapter, 1 spacer and case	11.4	5.2
7904SB	33794	Quick Draw 90™ Driver, 2 draw studs, 1 adapter, 1 spacer and case	10	4.5
7906SB	34300	Quick Draw 90™ Driver, 1/2" through 2" Slug-Buster® conduit size punches, dies and draw studs and case	14	6.4
7904E	34299	Metric - Quick Draw 90™ Driver, 2 draw studs, 1 adapter, 1 spacer and case	11	5.0
7904ESB	35615	Metric - Quick Draw 90™ Driver, Slug-Buster® Pg punches and dies 15.2 mm through 30.5 mm, 2 draw studs, 1 adapter, 1 spacer and case	11	5.0
7904ISO	35616	Metric - Quick Draw 90™ Driver, Slug-Buster® ISO punches and dies 16.2 mm through 40.5 mm, 2 draw studs, 1 adapter, 1 spacer and case	12.2	5.5

See next page for complete parts list for all kits.

STEEL CAPACITIES FOR CONDUIT SIZES

Required Draw Stud and Accessories	Standard Punches and Slug-Busters®							Slug-Splitters®			
	1/2"	3/4"	1-7/32" Oiltight	1"	1-1/4"	1-1/2"	2"	1/2"	3/4"	1-7/32" Oiltight	1-1/4"
3/8" Draw Stud											
Spacer & 7/16" Draw Stud											
Adapter & 7/16" Draw Stud											
Spacer & 3/4" Draw Stud											
3/4" Draw Stud											

10 GA. MILD STEEL

14 GA. MILD STEEL

10 GA. STAINLESS STEEL