

CU-RHH/RHW/USE

Conductor		Insulation Thickness (mils)	Nominal O.D. (mils)	Allowable Ampacities+			Approx. Net Weight Per 1000' (lbs.)	Standard Package
Size (AWG or kcmil)	No. Strands			60°C	75°C	90°C		
14	7	45	160	15	15	15	21	A
12	7	45	177	20	20	20	30	A
10	7	45	201	30	30	30	44	A
8	7	60	262	40	50	55	72	B
6	7	60	297	55	65	75	106	B
4	7	60	344	70	85	95	156	B
2	7	60	400	95	115	130	238	B
1	19	80	484	110	130	150	309	B
1/0	19	80	523	125	150	170	381	B
2/0	19	80	567	145	175	195	472	B
3/0	19	80	617	165	200	225	586	B
4/0	19	80	673	195	230	260	729	B
250	37	95	751	215	255	290	867	B
300	37	95	804	240	285	320	1029	B
350	37	95	854	260	310	350	1191	B
400	37	95	899	280	335	380	1352	B
500	37	95	983	320	380	430	1674	B
600	61	110	1089	355	420	475	2012	C
700	61	110	1158	385	460	520	2332	C
750	61	110	1191	400	475	535	2492	C
800	61	110	1223	410	490	555	2652	C
900	61	110	1283	435	520	585	2970	C
1000	61	110	1340	455	545	615	3288	C

+Allowable Ampacities:
Allowable ampacities shown are for general use as specified by the National Electrical Code, 2008 Edition, section 310.15.
60°C - When terminated to equipment for circuits rated 100 amperes or less or marked for 14 through 1 AWG conductors.
75°C - When terminated to equipment for circuits rated over 100 amperes or marked for conductors larger than 1 AWG.
90°C - RHH dry locations. RHW-2 and USE-2 wet or dry locations. For ampacity derating purposes.

STANDARD PACKAGE CODE:
A - 2500' Reel
B - 1000' Reel
C - 500' Reel

RECOMMENDED SAMPLE SPECIFICATIONS:

Conductors shall be UL-listed Tpe RHH or RHW-2 or USE-2, suitable for operation at 600 volts or less in wet or dry locations, including direct burial in the earth. Conductors shall be annealed copper, cross-linked polyethylene (XLP) insulated, as manufactured by Southwire Company or approved equal.



Copyright 2010, Southwire Company.
All Rights Reserved.

*Southwire is a registered trademark of Southwire Company.