

Alligator Clip with Cage Spring Barrel

Model # BU-61

Cage spring connection accepts standard prod needle (0.080 dia.)


Jaw opens 0.31" (7.9 mm) max



Material: nickel-plated steel clip, nickel-plated brass insert, gold plated beryllium copper cage spring

Length: 2.03" (51.59mm)

Rating: 10 Amps



Insulator for Alligator Clips

Model # BU-62-*

Protective flexible vinyl insulator for 60, 60C, 60CS, 60PR2, 60S,


60TBO, 60U, 60X and 61

Material: PVC

Length: 2.03" (51.59mm)

*Std. Colors: -0 Black, -2 Red,

-4 Yellow, -5 Green, -6 Blue, -9 White



Alligator Clip with Acetate Handle

Model # BU-60H-*

Compatible with all shrouded, unshrouded, or retractable 0.16" (4mm) banana plugs

Jaw opens 0.31" (7.9 mm) max

Material: nickel-plated steel clip; tenite

acetate insulated handle

Length: 2.23" (56.75mm)

*Std. Colors: -0 Black, -2 Red,

-4 Yellow, -5 Green, -6 Blue, -9 White

Rating: 10 Amps

Alligator Clip with Acetate Handle and Screw

Model # BU-60HS-*/BU-60CHS-*

Compatible with all shrouded, unshrouded, or retractable 0.16" (4mm) banana plugs

Jaw opens 0.31" (7.9 mm) max

Material: nickel-plated steel (BU-60HS-*) or solid copper (BU-60CHS-*) clip; tenite acetate insulated handle

Length: 2.34" (59.53mm)

*Std. Colors: -0 Black, -2 Red,

-4 Yellow, -5 Green, -6 Blue, -9 White

Federal Spec: AA59466-003 (red), AA59466-016 (black), (BU-

60CHS-*)

Rating: 10 Amps

Phone Tip Alligator Clip with Acetate Handle

Model # BU-60HPR-*

Accepts standard phone tip or test prod tip


Material: nickel-plated steel clip; tenite acetate insulated handle

Length: 2.23" (56.75mm)

*Std. Colors: -0 Black, -2 Red, -4 Yellow,

-5 Green, -6 Blue, -9 White

Rating: 10 Amps



Insulated Alligator Clip

Model # BU-63-*/BU-63C-*

BU-63-* same as BU-60S and includes a skin-tight, two-piece, flexible insulator

BU-63C-* same as BU-60CS and includes a skin-tight, two piece, flexible insulator

Compatible with all shrouded, unshrouded, or retractable 0.16" (4mm) banana plugs

Material: nickel-plated steel (BU-63-*) or solid copper (BU-63C-*); PVC insulator

Length: 2.25" (57.15mm)

*Std. Colors: -0 Black, -2 Red,

-4 Yellow, -5 Green, -6 Blue, -9 White

Rating: 10 Amps

