



Representative Image

Catalog No. 9T51B0107

Description: "1C,0.25kVA,120x240-12/24,80C,3R,60Hz,QB"

UPC No 783173008560

Home > Transformers > Dry Type, Encapsulated, Enclosed > Buck Boost

ABB's Buck-boost transformers are small, single phase, dry type distribution transformers designed and shipped as insulating/isolating transformers. They have a dual voltage primary and a dual voltage secondary. These transformers can be connected for a wide range of voltage combinations. The most common use is to buck (lower) or boost (raise) the supply voltage a small amount, usually 5 to 27%. Buck boost transformers comply with NEC Article 210-9, Exception 1, when field connected as an autotransformer.

Descriptors

Category	Buck Boost
GO Schedule	T6

Specifications

Phase	1
PriVoltage	120x240
SecVoltage	12/24
KVA	0.25 KVA
Coil Material	CU
TempRise	80.0 °C
ElecShield	N
SubType	BUCK BOOST
Frequency	60 Hz
FrameSize	8175
Net Weight	10
TempClass	180.0 °C
AmbTemp	40.0 °C
InsulSys	IS-12
EnergyEfficiency	None
KFactor	K1
Enclosure Type	NEMA 3R
Net Weight	10
Sound	Std
GSA Compliance	Yes

Classifications

UL	Yes
cUL	Yes
CE	No



Dimensions

Width	6.1 in
Depth	4.2 in
Height	7.4 in