



Representative

**Catalog Number:** OB 22  
**Product ID:** 7TAA263750R0035  
**UPC Number:** 78378674050  
**Status:** Active

Aluminum H-Type Compression Connectors, length 1-1/2 inch, die O..325-.162 inch on one side, .325-.162 on the other side

**North American Specifications (UNSPSC)**

UNSPSC	39121409 Wire connectors
IGCC	4543 Wire connectors
Brand Name	Blackburn
Type	Aluminum H-Type Compression Connector
Special Features	Pre-filled with oxide inhibitor to prevent oxidation and keep out moisture. Connectors Fully Marked with Installation and Compression location Information, providing easy Identification for easy Installation.
Application	Used to Dead End Aluminum, ACSR or Aluminum Alloy Conductors.
Standard	RUS Accepted. Complies with ANSI C119.4 Specifications
Size	Length 1-1/2 inches
Connection	Compression/Crimp
Wire Size	Diameter Main - .162-.325, Tap - .162-.325, C .062-.148
Number Of Conductors	3
Material	Aluminum
Voltage Rating	None since Uninsulated
Insulation	None
Temperature Rating	up to 90 Degrees C.
Mounting	None
Environmental Conditions	All Seasons / Conditions

**Packaging**

Inner Quantity	25
Inner Dimensions (inches)	2.25x5x9.687
Outer Quantity	250
Outer Dimensions (inches)	11.6x10.6x10.5
Weight Uom	8.5 lbs. per 100

**Documents / Support Tools**

Technical Drawing / Data Sheet Canada	Available on Website
Safety Data Sheet (SDS) Global	SDS-00057-TB2

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
www.tnb.com

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com