

Bore-Gard® – UL Listed/RUS Listed

Carlon Bore-Gard is designed and proven to meet the rigorous requirements of horizontal directional drilling for electrical and datacom applications. Its unique design incorporates a water-tight seal and locking ring that enables fast, cement-free assembly. Bore-Gard is strong enough for 1000 ft. bores and is available in convenient 10 and 20- foot lengths...ideal for tight spaces and easy to transport to the job-site.

Part No.	Description			
BG340SP-010	3" Schedule 40 Bore-Gard – 10 ft. Length			
BG340SP-020	3" Schedule 40 Bore-Gard – 20 ft. Length			
BG440SP-010	4" Schedule 40 Bore-Gard – 10 ft. Length			
BG440SP-020	4" Schedule 40 Bore-Gard – 20 ft. Length			
BG540SP-010	5" Schedule 40 Bore-Gard – 10 ft. Length			
BG540SP-020	5" Schedule 40 Bore-Gard – 20 ft. Length			
BG640SP-010	6" Schedule 40 Bore-Gard – 10 ft. Length			
BG640SP-020	6" Schedule 40 Bore-Gard – 20 ft. Length			
BG380SP-010	3" Schedule 80 Bore-Gard – 10 ft. Length			
BG380SP-020	3" Schedule 80 Bore-Gard – 20 ft. Length			
BG480SP-010	4" Schedule 80 Bore-Gard – 10 ft. Length			
BG480SP-020	4" Schedule 80 Bore-Gard – 20 ft. Length			



Boreable Multi-Gard®

Carlon Boreable Multi-Gard PVC conduit combines the same unique features as Bore-Gard with the convenience of a multi-cell conduit. Boreable Multi-Gard is able to bore up to 500 feet without labor-intensive operations. It's available in 3-way and 4-way configurations and comes in convenient 10 and 20-foot lengths... ideal for tight spaces and easier to transport to the job-site.

Part No.	Description	
MFSS3B-020	3-Way Boreable Multi-Gard – 20 ft. Length	
MFSS4B-020	4-Way Boreable Multi-Gard – 20 ft. Length	



Pulling Eyes

Carlon Pulling Eyes have a permanent outer sleeve and a seal on pipe O.D. Ideal for Bore-Gard and Boreable Multi-Gard

Part No.	Description
BG3PE	3" Pulling Eye
BG4PE	4" Pulling Eye
BG5PE	5" Pulling Eye
BG6PE	6" Pulling Eye

Locking Straps

Gaskets

Size	Part No.	Std. Ctn. Qty.	Part No.	Std. Ctn. Qty.
3"	GSUP3	1	HBOR3	1
4"	GSUP	1	HBOR	1
5"	GSUP5	1	HBOR5	1
6"	GSUP6	1	HBOR6	1