

High Temperature Wire-Nut® Wire Connectors

All of the Wire-Nut® Wire Connector features plus:

- Black, thermoplastic shell specially designed to withstand the extreme heat build-up commonly found in high-wattage light fixtures and signs. UL Listed to 150°C (302°F)
- Four models to cover wire ranges from 22 through 12 AWG




Model	Color	Wire Combination Range	Wire Combination Range (mm)	Quantity	Cat. No.
71B®	Black	300V 22 to 16 AWG Min. 2 #22 Str Max. 2 #16	300V ,34mm² to 1,5mm² Min. 2-,34mm² Max. 2-1,5mm²	Carton of 1,000	30-151
				Keg of 25,000 (loose pack)	30-251
72B®	Black	300V 22 to 14 AWG Min. 2 #22 Max. 3 #16	300V ,34mm² to 2,5mm² Min. 2-,34mm² Max. 3-1,5mm²	Carton of 1,000	30-152
				Keg of 10,000 (loose pack)	30-252
73B®	Black	600V* 22 to 14 AWG Min. 1 #18 w/1 #20 Max. 4 #16 & 1 #20	600V* ,34mm² to 2,5mm² Min. 1-,75mm² w/1-,50mm² Max. 4-1,5mm² w/1-,50mm²	Carton of 1,000	30-153
				Keg of 10,000 (loose pack)	30-253
59B™	Black	600V* 22 to 12 AWG Min. 2 #20 Max. 3 #14	600V* ,34mm² to 4,0mm² Min. 2-,5mm² Max. 3-2,5mm²	Box of 100	30-059
				Carton of 1,000	30-159
				Keg of 5,000 (loose pack)	30-259

*1,000V maximum in fixtures and signs



Dimensions (Inches/mm)



Model	A	B	C	D	E
71B® Black	5/32 4	1/4 6.5	21/64 8	13/64 5	37/64 15
72B® Black	13/64 5	5/16 8	25/64 10	15/64 6	45/64 18
73B® Black	13/64 5	23/64 9	7/16 11	3/8 9.5	55/64 22
59B™ Black	13/64 5	13/32 10	31/64 12	37/64 14.5	1-1/16 27