



**MILBANK**  
ENERGY AT WORK

## U5100-XL-11GR



<b>Catalog Number</b>	U5100-XL-11GR	<b>Insulation</b>	Glass Polyester
<b>Marketing Product Description</b>	4 Terminal Ring Type Small Closing Plate 520GR 520GR Surface Mount	<b>Mounting</b>	Surface Mount
<b>UPC</b>	784572265509	<b>Enclosure</b>	G90 Galvanized Steel with Powder Coat Finish
<b>Length (IN)</b>	5.188	<b>Jaw Quantity</b>	4 Terminal
<b>Width (IN)</b>	8.875	<b>Bypass Type</b>	No Bypass
<b>Height (IN)</b>	25	<b>Number of Meter Positions</b>	Single Power Head
<b>Brand Name</b>	Milbank	<b>Equipment Ground</b>	Ground Bar
<b>Type</b>	Ring Type Meter Socket	<b>Hub Opening</b>	Small Closing Plate
<b>Special Features</b>	Two Single Pole 20 Ampere Breakers	<b>Line Side Wire Range</b>	6 AWG - 350 kcmil
<b>Application</b>	RV Power	<b>Number Branch Circuits</b>	4
<b>Standard</b>	UL Listed;Type 3R	<b>Number Of Receptacles</b>	2
<b>Voltage Rating</b>	Up to 240 Volts Alternating Current	<b>Receptacle Configuration</b>	Two NEMA 5-20 Ground Fault
<b>Amperage Rating</b>	125 Continuous Ampere		
<b>Phase</b>	1 Phase		
<b>Frequency Rating</b>	60 Hertz		
<b>Size</b>	5.188L x 8.875W x25H		
<b>Number Of Cutouts</b>	2		
<b>Cutout Size</b>	Two Single Pole 20 Ampere Breakers		
<b>Cable Entry</b>	Overhead or Underground		
<b>Terminal</b>	Lay in		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.