

Part Number System for Spiral Wrap

T	25	F	-	C	16
Type	Outside Diameter	Material		Package Size	Color Suffix
T = Spiral Wrap	12 = 1/8"	F = Polyethylene		X = 10'	See Table Below
	25 = 1/4"	R = Fire Resistant Polyethylene		Q = 25'	
	38 = 3/8"	FR = Flame Retardant Polyethylene		L = 50'	
	50 = 1/2"	N = Nylon		C = 100'	
	62 = 5/8"	T = TEFLON‡		T = 200'	
	75 = 3/4"			TL = 250'	
	100 = 1"			D = 500'	
				M = 1000'	

MATERIAL AVAILABILITY						
Color	Color Suffix	Polyethylene	Fire Resistant Polyethylene	Flame Retardant Polyethylene	Nylon 6.6	TEFLON‡
Natural*	No Suffix will be listed	✓	✓ *	✓ *	✓	✓
Weather Resistant Black	0	✓			✓	
Brown	1	✓				
Red	2	✓				
Orange	3	✓				
Yellow	4	✓				
Green	5	✓				
Blue	6	✓				
Purple	7	✓				
Gray	8	✓				
White	10	✓				
Pink	16	✓				
Black	20	✓	✓	✓		

Blank = Not applicable

‡TEFLON or equivalent fluoropolymer PTFE material is used. TEFLON is a registered trademark of E.I. du Pont de Nemours and Company.

*Natural can range from transparent, opaque, to white

A. System Overview

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power & Grounding Connectors

E1. Labeling System

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Lockout/Tagout & Safety Solutions

F. Index

A. System Overview

Spiral Wrap

- Harness multiple cables into a single manageable bundle
- Allows breakouts of single/multiple cables
- Provides protection for cables
- Multiple colors allow easy identification of cable bundles
- Installation tool supplied in each package

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel



C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power & Grounding Connectors

E1. Labeling System

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Lockout/Tagout & Safety Solutions

F. Index

Part Number	Material	Color	Length Per Reel		Bundle Diameter Range		Outside Diameter		Temperature Range	Wall Thickness		Std. Pkg. Qty.
			ft	M	In.	mm	In.	mm		In	mm	
T12F-C	Polyethylene	Natural	100	30.5	1/16 to 1/2	1.6 to 12.7	.12	3.3	-40°F to 122°F (-40°C to 50°C)	.03	.76	1
T19F-C			100	30.5	1/8 to 1	3.2 to 25.4	.19	4.8		.03	.89	1
T25F-X			10	3.05	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C1		Brown	100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C10			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C16			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C2			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C3		Orange	100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C4			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C5			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C6			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C7		Purple	100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C8			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T38F-C			100	30.5	5/16 to 3	7.9 to 76.2	.38	9.5		.05	1.40	1
T50F-X			10	3.05	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C	Polyethylene	Natural	100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C1			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C10			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C16			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C2		Pink	100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C3			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C4			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C5			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C6		Red	100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C7			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C8			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T62F-C		Gray	100	30.5	1/2 to 4 1/2	12.7 to 114.3	.62	15.9		.06	1.57	1
T75F-C			100	30.5	5/8 to 5	15.9 to 127.0	.75	19.1		.06	1.65	1
T100F-C			100	30.5	7/8 to 6	22.2 to 152.4	1.00	25.4		.07	1.78	1

Reel packaging may contain splices. Contact Customer Service for further information.

Spiral Wrap (continued)

Part Number	Material	Color	Length Per Reel		Bundle Diameter Range		Outside Diameter		Temperature Range	Wall Thickness		Std. Pkg. Qty.
			ft	M	In.	mm	In.	mm		In	mm	
T12F-C0	Weather Resistant Polyethylene	Black	100	30.5	1/16 to 1/2	1.6 to 12.7	.12	3.3	-40°F to 122°F (-40°C to 50°C)	.03	.76	1
T19F-C0			100	30.5	1/8 to 1	3.2 to 25.4	.19	4.8		.03	.89	1
T25F-X0			10	3.05	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25F-C0			100	30.5			.25	6.4		.04	1.02	1
T38F-C0			100	30.5	5/16 to 3	7.9 to 76.2	.38	9.5		.05	1.40	1
T50F-X0			10	3.05	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50F-C0			100	30.5			.50	12.7		.06	1.50	1
T62F-C0			100	30.5	1/2 to 4 1/2	12.7 to 114.3	.62	15.9		.06	1.57	1
T75F-C0			100	30.5	5/8 to 5	15.9 to 127.0	.75	19.1		.06	1.65	1
T100F-C0			100	30.5	7/8 to 6	22.2 to 152.4	1.00	25.4		.07	1.78	1
T12R-C	Fire Resistant Polyethylene	Natural	100	30.5	1/16 to 1/2	1.6 to 12.7	.12	3.3	-40°F to 122°F (-40°C to 50°C)	.03	.76	1
T19R-C			100	30.5	1/8 to 1	3.2 to 25.4	.19	4.8		.03	.89	1
T25R-C			100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25R-C20		Black	100	30.5			.25	6.4		.04	1.02	1
T38R-C			100	30.5	5/16 to 3	7.9 to 76.2	.38	9.5		.05	1.40	1
T50R-C			100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T62R-C		Natural	100	30.5	1/2 to 4 1/2	12.7 to 114.3	.62	15.9		.06	1.57	1
T75R-C			100	30.5	5/8 to 5	15.9 to 127.0	.75	19.1		.07	1.65	1
T100R-C			100	30.5	7/8 to 6	22.2 to 152.4	1.00	25.4		.07	1.78	1
T12FR-C			100	30.5	1/16 to 1/2	1.6 to 12.7	.12	3.3		.03	.76	1
T12FR-C20	Flame Retardant Polyethylene*	Black	100	30.5	1/16 to 1/2	1.6 to 12.7	.12	3.3	-40°F to 140°F (-40°C to 60°C)	.03	.76	1
T19FR-C		Natural	100	30.5	1/8 to 1	3.2 to 25.4	.19	4.8		.03	.89	1
T19FR-C20		Black	100	30.5	1/8 to 1	3.2 to 25.4	.19	4.8		.03	.89	1
T25FR-C		Natural	100	30.5	3/16 to 2	4.8 to 50.4	.25	6.4		.04	1.02	1
T25FR-C20		Black	100	30.5			.25	6.4		.04	1.02	1
T38FR-C		Natural	100	30.5	5/16 to 3	7.9 to 76.2	.38	9.5		.05	1.40	1
T38FR-C20		Black	100	30.5			.38	9.5		.05	1.40	1
T50FR-C		Natural	100	30.5	3/8 to 4	9.5 to 101.6	.50	12.7		.06	1.50	1
T50FR-C20		Black	100	30.5			.50	12.7		.06	1.50	1
T62FR-C		Natural	100	30.5	1/2 to 4 1/2	12.7 to 114.3	.62	15.9		.06	1.57	1
T62FR-C20		Black	100	30.5			.62	15.9		.06	1.57	1
T75FR-C		Natural	100	30.5	5/8 to 5	15.9 to 127.0	.75	19.1		.06	1.65	1
T75FR-C20		Black	100	30.5			.75	19.1		.06	1.65	1
T100FR-C		Natural	100	30.5	7/8 to 6	22.2 to 152.4	1.00	25.4		.07	1.78	1
T100FR-C20		Black	100	30.5			1.00	25.4		.07	1.78	1

*Flame retardant products are manufactured from a material that is rated UL94V-0.
Reel packaging may contain splices. Contact Customer Service for further information.

A. System Overview

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power & Grounding Connectors

E1. Labeling System

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Lockout/Tagout & Safety Solutions

F. Index