

BZE6-2RQ2



Actual product appearance may vary.

**Enclosed Switches Series
E6: Top Roller Arm
Actuator, Adjustable with
Steel Roller; 1NC 1NO
SPDT Snap Action; 0.5 in -
14NPT conduit**

Product Specifications

Availability	Global
Operating Force (OF)	2,78 N to 5,00 N [10 oz to 18 oz]
Release Force	1,67 N [6 oz] min.
Pretravel (PT)	4,78 mm [0.188 in] max.
Overtravel (OT)	5,56 mm [0.219 in] min.
Differential Travel (DT)	0,15 mm [0.006 in] max.
Product Type	Enclosed Switches
Actuator	Top Roller Arm
Lever Type	Roller - Adjustable
Circuitry	1NC 1NO SPDT Snap Action
Ampere Rating	15 A Ind./2 A Ind./0.5 A Res./0.25 A Res.
Supply Voltage	125 Vac, 250 Vac, 480 Vac/600 Vac/125 Vdc/250 Vdc
Housing Material	Zinc Die-Cast
Termination Type	0.5 in - 14NPT Conduit
Housing Type	Split Housing, Side Mount
Series Name	E6/V6
Sealing	IP40; NEMA 1
UL File #	E12252
Operating Temperature	-32 °C to 71 °C [-25 °F to 160 °F]