



Representative Image

Catalog No. U058C

Description: 80A SURFACE UNMTRD 50/30

UPC No 784567570809

Home > Power Outlets > Power Outlets

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors

Category	Power Outlets
----------	---------------

Specifications

Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	14-50R(BR54U) TTR-30(R32U)
Feed	Overhead
AIC	10,000
Amps	80
Cabinet Size	6 in. W X 14 in. H
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	CB250 CB130
Load Center	LC33N1
Loop Feed	No
Phase	1
Suitable for Service Equipment	Yes
Unit Weight	9 lb
Volts	120/240

Classifications

Standard Package	1
Stock Class Code	Non Stock

Approvals

Certification	UL/CUL
---------------	--------

Publications

Title	Publication No.	Publication Type
Heavy Duty Power Outlets 2 pages. MET-020 Rev. B.	MET-020A	Brochures

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.