

Three Phase C Face Motors

Totally Enclosed - General Purpose

Three Phase - Totally Enclosed - C Face Less Base

HP	SYN RPM 60 Hz	NEMA Frame	▼ Catalog Number	Stock	Model Number	App. Wgt. (lbs)	Voltage	F. L. Amps @ 230 V	% F.L. Eff.	Service Factor	"C" Dim. (Inches)	♥ Notes
3	3600	145TC	G120993.00	✓	C145T34FC39	60	208-230/460	8.4	85.5	1.15	13.42	S, US
	3600	145TC	LM32848	✓	SSF2S3TCN61	40	208-230/460	7.6	85.5	1.15	13.42	S, US
	3600	56C	111630.00	✓	C6T34FC28	37	208-230/460	7.6	84.0	1.15	12.81	S, US
	3600	182TC	G131513.00	✓	C182T34FC6	55	208-230/460	8.0	84.0	1.15	13.97	S, MX
	3600	182TC	199082.00	✓	C182T34FC1	83	230/460	7.6	86.5	1.15	15.75	C, CN
	1800	182TC	G131491.00	✓	C182T17FC35	67	208-230/460	8.2	87.5	1.15	13.96	S, MX
	1800	182TC	199083.00	✓	C182T17FC1	87	230/460	7.8	89.5	1.15	15.75	C, CN
	1800	182TC	LM16298	D	AAF4P3TCN61	91	230/460	8.4	87.5	1.25	14.94	A, US
	1800	182TC	LM33574	✓	AAF4P3TCN61AP26	91	230/460	8.4	87.5	1.25	14.96	A, MX
	1800	56C	113890.00	✓	C6T17FC91	43	208-230/460	8.6	82.5	1.00	13.81	S, US
5	3600	182TC	LM33337	✓	SSF4P3TCN61	67	230/460	8.2	87.5	1.15	13.96	S, MX
	1800	182TC	131503.00	✓	C182T17FC26	72	208-230/460	7.8	89.5	1.15	14.96	S, MX
	1800	182TC	LM16824	D	AAF4B3TCN61	95	230/460	8.0	89.5	1.25	15.94	A, US
	1800	182TC	LM33573	✓	AAF4B3TCN61AP21	95	230/460	8.0	89.5	1.25	14.96	A, MX
	1200	213TC	G141114.00	✓	C213T11FC1	133	208-230/460	14.4	87.5	1.15	17.71	S, MX
	3600	184TC	G131514.00	✓	C184T34FC23	79	208-230/460	12.0	87.5	1.15	14.47	S, MX
	3600	184TC	199084.00	✓	C184T34FC1	95	230/460	13.4	88.5	1.15	16.73	C, CN
	1800	184TC	G131492.00	✓	C184T17FC46	80	208-230/460	12.8	87.5	1.15	14.97	S, MX
	1800	184TC	199085.00	✓	C184T17FC1	110	230/460	12.4	89.5	1.15	16.73	C, CN
	1800	184TC	LM16299	D	AAF4P5TCN61	104	230/460	13.0	87.5	1.25	15.94	A, US
7 1/2	3600	184TC	LM33489	✓	AAF4P5TCN61AP26	104	230/460	13.0	87.5	1.25	15.94	A, MX
	1800	184TC	131501.00	✓	C184T17FC29	90	208-230/460	12.8	89.5	1.15	15.97	S, MX
	1200	215TC	G140535.00	✓	C215T11FC3	142	208-230/460	17.6	87.5	1.15	18.21	S, MX
	3600	184TC	G131510.00	✓	C184T34FC22	90	208-230/460	16.8	88.5	1.00	15.97	S, MX
	3600	S213TC	G131912.00	✓	C184T34FC24	91	208-230/460	16.8	88.5	1.00	16.96	S, MX
	3600	213TC	G151345.60	✓	C213T34FC43	158	208-230/460	17.8	88.5	1.25	18.95	C, CN
	3600	213TC	199086.00	✓	C213T34FC1	116	230/460	17.8	89.5	1.15	19.53	C, CN
	1800	213TC	G141113.00	✓	C213T17FC9	144	208-230/460	20.4	89.5	1.15	17.71	S, MX
	1800	213TC	G151346.60	✓	C213T17FC42	148	208-230/460	19.2	89.5	1.25	18.95	C, CN
	1800	213TC	199087.00	✓	C213T17FC1	143	230/460	18.6	91.7	1.15	19.53	C, CN
10	3600	213TC	140486.00	✓	C213T17FC7	144	208-230/460	21.4	91.7	1.25	18.70	S, MX
	3600	213TC	G140690.00	✓	C215T34FC4	112	208-230/460	23.6	90.2	1.15	20.57	S, MX
	3600	215TC	G151347.60	✓	C215T34FC43	153	208-230/460	23.6	90.2	1.25	20.36	C, CN
	3600	215TC	199088.00	✓	C215T34FC1	137	230/460	22.8	90.2	1.15	21.02	C, CN
	1800	215TC	G140109.00	✓	C215T17FC10	158	208-230/460	26.0	89.5	1.15	20.57	S, MX
	1800	215TC	140484.00	✓	C215T17FC4	160	208-230/460	26.6	91.7	1.25	19.70	S, MX
	1800	215TC	G151348.60	✓	C215T17FC42	173	208-230/460	25.2	91.0	1.25	20.36	C, CN
	1800	215TC	199089.00	✓	C215T17FC1	168	230/460	24.4	91.7	1.15	21.02	C, CN
	1800	215TC	LM16301	✓	AF4P10TCN61	149	230/460	27.0	89.5	1.25	19.63	A, US

Green items are Premium Efficient

♥ Note listing on inside back flap

▼ LM Numbers are Lincoln Models

Continued On Next Page

D - To be discontinued when inventory is depleted

Specifications are subject to change without notice



View On-line Technical Information

