



## Ball & Roller Bearing Hi-Temp Industrial Grease, 14 Wt Oz

No. SL3630 | Item# 1007957 | Case# 1007956

### Product Description

A special blend of treated petroleum base stocks, rust & oxidation inhibitors, extreme pressure additives combined with an aluminum complex thickener. It will not wash out, splatter or run out under severe loads. Friction and wear are greatly reduced.

### Applications

Ball & Roller bearings, cement equipment, chassis points, construction applications, disc brake wheel bearings, heavy duty truck bearings, heavy loaded bushings, ideal for apps operating at intermittent temps up to 400 F, paper mills, steel mills

### Unit Package Description

14 Ounce Cartridge

### Brand

Sta-Lube

### Generic Description 1

Ball & Roller Bearing Grease

### Net Fill

14 Wt Oz

### UPC Code

072213363005

### Unit Dimensions

9.31H x 2.13W x 2.13D in

### Units Per Case

10

### Case Dimensions

9.5H x 4.5W x 11.38D in

### Cases Per Pallet

150

### Case Weight

11 lbs

### I 2 of 5 Code

30072213363006

### Appearance

Dark Gray Semi-Solid to Solid Grease

### Base Type

Aluminum Complex

### Flash point (F)

400°F

### Flash point (C)

204°C

### Flammability Class - CPSC

None

### Spec Gravity Concentrate

0.9 at 60°F

### NLGI Grade

2

### Timken OK Load Lbs.

40 Lbs

### Plastic Safe

Not Determined

### Evaporation Rate

<0.01 (Butyl Acetate=1)



Last revised: 4/23/2019  
Page 1 of 2



**Chemical Solutions to Keep You Moving™**  
f t y i n • 800-272-8963 • [crcindustries.com](http://crcindustries.com)

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Working Temp (F)	0 to 325°F
Working Temp (C)	-18 to 162°C
4 Ball EP	58 LWI, 250 KG Weld
4 Ball Wear	0.9 mm max
Drop Point	485°F
Oil Separation	<10%
Oxidation Stability	5
Pour Point (F)	15°F
Pour Point (C)	-9.44°C
ISO Viscosity Grade	575
Water Washout	0.3
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0.3
VOC g/L (Consumer Product def)	2.7
VOC lbs/gal (Consumer Prod def)	0.022
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 4/23/2019  
Page 2 of 2



**Chemical Solutions to Keep You Moving™**  
f t y o i n • 800-272-8963 • [crcindustries.com](http://crcindustries.com)

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.