

BZE6-2RQ8



**Enclosed Switches Series E6: Top
Roller Plunger Actuator; 1NC 1NO
SPDT Snap Action; 0.5 in - 14NPT
conduit**

*Actual product appearance
may vary.*

Product Specifications

| | |
|--------------------------|--|
| Availability | Global |
| Operating Force (OF) | 2,50 N to 3,61 N [9 oz to 13 oz] |
| Release Force | 1,11 N [0.25 lb] min. |
| Pretravel (PT) | 0,38 mm [0.015 in] max. |
| Overtravel (OT) | 3,55 mm [0.140 in] min. |
| Differential Travel (DT) | 0,05 mm [0.002 in] max. |
| Product Type | Enclosed Switches |
| Actuator | Top Roller Plunger |
| Circuitry | 1NC 1NO SPDT Snap Action |
| Ampere Rating | 15 A Ind./2 A Ind./0.5 A Res./0.25 A Res. |
| Supply Voltage | 125 Vac, 250 Vac, 480 Vac/600 Vac/125 Vdc/250 Vdc |
| Housing Material | Zinc Die-Cast |
| Termination Type | 0.5 in - 14NPT Conduit |
| Housing Type | Split Housing, Side Mount |
| Series Name | E6/V6 |
| Sealing | IP40; NEMA 1 |
| UL File # | E12252 |
| Operating Temperature | -32 °C to 71 °C [-25 °F to 160 °F] |
| Comment | Without seal boot on plunger, Roller parallel to long axis of switch |