



Ceramalux Instant Restrike

C150S55/2 12PK


Dual arc-tube delivers 40,000 hour rated average life as compared to 24,000 hour rated average life for standard HPS lamps. Ideal for industrial applications, warehouses, post top applications and parking lots.

Product data

General Information		Mechanical and Housing			
Operating Position	UNIVERSAL [Any or Universal (U)]	Bulb Finish	Clear		
Cap-Base	E39 [Single Contact Mogul Screw]	Bulb Material	Hard Glass		
Bulb Shape	ED-23 1/2				
Light Technical			Approval and Application		
Chromaticity Coordinate X (Nom)	514	Mercury (Hg) Content (Max)			
Chromaticity Coordinate Y (Nom)	424	34 mg			
Correlated Color Temperature (Nom)	2100 K				
Luminous Efficacy (Rated) (Min)	96 lm/W	Product Data			
Luminous Efficacy (rated) (Nom)	106 lm/W	Order product name	C150S55/2 12PK		
Color rendering index (CRI)	21	Order code	928601145601		
Operating and Electrical			Numerator - Quantity Per Pack	1	
Power Consumption	150.6 W	Numerator - Packs per outer box	12		
Lamp Current (Nom)	3.2 A	Material number (12NC)	928601145601		
Voltage (Nom)	55 V	Full product name	C150S55/2 12PK		
Voltage (Nom)	55 V	EAN/UPC - Case	50046677265613		

Ceramalux Instant Restrike

Dimensional drawing



Product	D	C (max)
C150S55/2 12PK	2.938 inch	7.75 inch

