



Representative Image

Catalog No. TLM1620CCU

Description: FLD CNVRTB 200A 16CRK 22K IC COMB

UPC No 783164112382

Home > Load Centers > Residential Load Centers

(Panelboards No. 67) 60 degree/75 degree centrigrade Conductor Rating Suitable for use as service entrance equipment when Installed in accordance with the National Electrical Code 22kAIC RMS symmetrical, Except Where Noted 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down For a listing of CSA Listed load centers, visit www.geelectrical.com Amperage 200 A

Descriptors			
Category	Residential Load Centers		
GO Schedule	RD		
Grouping	Single Phase - USA		

Specifications	
Туре	Standard
Interrupting Capacity Rating	65
Amperage	200 A
Device type	Convertible
Enclosure	Indoor Type 1 Enclosure, Combination
Phase	1 Phase
Socket Type	0
1" Space	16
1/2" Space	42 4 24 16 20 32 40
Feed	Either
Door	Yes
GSA Compliance	No
Input/Output Voltage	120/240V ac

Classifications	
UL/CUL Listing	UL

electrification.us.abb.com Created on: 09/30/2020

Publications		
Title	Publication No.	Publication Type
PowerMark Gold* Load Centers, Q-Line Circuit Breakers and Accessories Guide mber selection guide, knockout drawings, wiring diagrams, accessories and options list Only available on-line.	DET1023	Application and Technical
Outline Drawing Indoor Load Center	10103091SH18	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.

electrification.us.abb.com Created on: 09/30/2020