



# Switch Start Metal Halide Standard

## MH175/U/M 12PK

High performance, Long life and Superior light quality. A compact, energy efficient metal halide lamp that provides crisp, sparkling light with long life and high efficiency.

### Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

### Product data

General Information		Operating and Electrical	
Operating Position	UNIVERSAL [Any or Universal (U)]	Lamp Current (Nom)	1.5 A
Cap-Base	E26 [Single Contact Medium Screw]	Voltage (Nom)	132 V
Light Technical			Mechanical and Housing
Color Code	640 [CCT of 4000K]	Bulb Finish	Clear
Color Designation	Cool White (CW)	Bulb Material	Hard Glass
Chromaticity Coordinate X (Nom)	0.385	Bulb Shape	BD17
Chromaticity Coordinate Y (Nom)	0.390		
Correlated Color Temperature (Nom)	4000 K		
Luminous Efficacy (Rated) (Min)	70 lm/W	Approval and Application	
Luminous Efficacy (rated) (Nom)	80 lm/W	Energy Saving Product	Not Applicable
Color rendering index (CRI)	65	Mercury (Hg) Content (Max)	24.0 mg

# Switch Start Metal Halide Standard

## Product Data

Order product name	MH175/U/M 12PK
Order code	928601122311
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

## Material number (12NC)

928601122311

## Full product name

MH175/U/M 12PK

## EAN/UPC - Case

50046677313581

## Dimensional drawing

Product	D	C (max)
MH175/U/M 12PK	2.125 inch	5.438 inch

