LITHONIA LIGHTING®

Catalog Number	
Notes	
Type	

FEATURES & SPECIFICATIONS

INTENDED USE — Recessed housing rated IC or Non-IC. For new construction only.

Approved for all ceiling and wiring types.

Approved for direct burial in insulation.

CONSTRUCTION — Air-tight standard. Tested to meet current energy codes.

Aluminum housing with galvanized steel pan.

Galvanized bar hangers span up to 24" o.c. and feature stepped shank nail and positioning guide with integral T-bar locks. Two locking screws hold fixture in position.

Galvanized steel junction box with four built-in Romex clamps. Four 1/2" and two 3/4" knockouts with slots for pryout. Rated for through branch wiring.

Maximum 4 (2 in, 2 out) No. 12 AWG conductors. Rated for 90°C.

Ground wire provided.

Removable J-box doors for easy access.

ELECTRICAL — Durable medium-base porcelain socket with nickel plated copper alloy screw shell and contact.

Socket clips to top of housing to prevent paint overspray in socket screw shell.

Socket attaches to reflector to ensure proper and consistent lamp position.

Thermal protection provided against improper lamp usage.

120 volt only.

INSTALLATION — Air-tight housing suitable for air-tight installations. Refer to energy codes for proper installations.

2x8 and 2x6 wood joist or T-bar installation.

Expandable bar hangers allow for off-center mounting in wood joist or T-bar ceilings. Length of 25-1/2" maximum 13-1/4" minimum or cut to fit 5-1/2" on center joist construction.

Vertical adjustment of housing allows for flush mounting with ceiling face.

Suitable for ceilings up to 1-1/2" thick.

LISTINGS — UL Listed to US and Canadian safety standards. Damp location listing (See trim selection for wet location listing).

WARRANTY — 1-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

4" Housing


L3


INCANDESCENT

IC/Non-IC

New Construction







Specifications

Height: 5-1/4 (13.3)

Length: 13-1/4 (33.7)

Width: 12-3/16 (30.9)

Ceiling opening: 4 (10.2)

All dimensions are inches (centimeters) unless otherwise specified.

ORDERING INFORMATION For shortest lead times, configure product using **bolded options.**

Example: L3 R6

L3		
Series	**Options**	**Packaging**
L3	Shipped installed in fixture PHC Poke-home wire connector GSKT Foam gasketing. Aids in air-tight installation.	**R6** Resale pack of six **U** Unit

Notes

See trim summary on reverse side for maximum wattages.


L3 4" New Construction Housing

Description
Catalog number — Maximum wattage[1]

General/Task

Open Narrow Flange

301 White
301MW Matte white
301A Clear diffuse, white plastic flange
301AZ Clear specular anodized
301BLZ Black specular anodized



IC 30 R20, 35 PAR20
Non IC 50 PAR20

Baffle Narrow Flange

3B1W White
3B1MW Matte white



IC 50 PAR20, 50 R20

Baffle Deep Narrow Flange

3B2W White



IC 30 R20, 35 PAR20
Non IC 50 R20

Accent/Wallwash

Eyeball Narrow Flange

3E1MW Matte white



IC 50 PAR20, 50 R20

Notes
1 Maximum wattage listed. Lower wattage lamps may be used.
2 All trims are damp location listed.

LED Gimbal Module (Damp location)

5 YEAR warranty · DIMMABLE LED · DAMP LOCATION™

Example: 4G1MB LED L3[1]

ORDERING INFORMATION For shortest lead times, configure product using **bolded options.**

4G1			LED		
Series/Finish			**Lamps**	**CCT / CRI / W / Lumens[2]**	**Voltage**
Series		Finish	**LED**	30K 90CRI 3000K / 93CRI / 7.7W / 500L	**(blank)** 120V
4G1	4" Gimbal module	**MB** Matte black[2]		40K 90CRI 4000K / 94CRI / 8W / 560L	
		BN Brush nickel[2]			

Notes
1 L3 must be ordered on separate line.
2 Total system delivered lumens.

LITHONIA LIGHTING®
An AcuityBrands Company
DOWNLIGHTING: One Lithonia Way, Conyers, GA 30012 Phone: 1-800-705-SERV (7378) www.lithonia.com
© 2000-2025 Acuity Brands Lighting, Inc. All rights reserved.
Rev. 05/08/25