



Representative Image

Catalog No. TH3363SS316**Description: 100A 3P HD N4X SS316 600V FUSIBLE****UPC No 783164382334****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. NEMA type 4X enclosure grade 316 stainless steel. TH3363SS

Descriptors

Category	Heavy Duty
GO Schedule	S1

Specifications

Voltage	600 AC
Amperage	100 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 4/4X (316 Stainless)
Options	None
Wire Range (Cu/Al)	14-1/0 CU;12-1/0 AL
480 Vac, NEC Std, 1-ph	10
480 Vac, NEC Std, 3-ph	25
480 Vac, Time Delay, 1-ph	30
480 Vac, Time Delay, 3-ph	60
600 Vac, NEC Std, 1-ph	3
600 Vac, NEC Std, 3-ph	30
600 Vac, Time Delay, 1-ph	40
600 Vac, Time Delay, 3-ph	75
250 Vdc	20
GSA Compliance	Yes

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	25.4
--------	------

by **ABB**

Dimensions

Depth	5.2
Width	13.4
Weight	36

Publications

Title	Publication No.	Publication Type
200A (incl. 316 Stainless) - Safety Switches 1 page outline drawing in .pdf format.	10103091SH113	Drawings-Outline and Dimensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.