



Key Features

- Tough Die-Cast Aluminum Housing
- 6 Year Warranty
- UL Listed
- 2000 & 3000 Watt Ratings
- 30-45 Second "On" & "Off" Delay

The AT's rugged die-cast aluminum housing makes it the ideal choice for any outdoor installation where vandalism or other types of abuse may be a concern. These controls feature a heavy-duty thermal bi-metal switch that provides a 30-45 second time delay. This virtually eliminates unwanted lamp cycling that could be caused by lightning, car headlights or other sudden changes in the ambient light level. Although the turn-on level is pre-set at the factory, each AT control is furnished with an adjustable slide bar that allows field adjustment to satisfy specific needs.

Model	Rated Volts	Range (Volts)	Load Rating Tungsten (Watts)	Load Rating Ballast (VA)	Turn On (Fc)	Off/On Ratio
AT-15	120	105-130	2000	1900	1.5 +/- 0.5	4 : 1
AT-168	240	185-305	2000	1900	1.5 +/- 0.5	4 : 1
AT-19	480	420-530	2000	1900	1.5 +/- 0.5	4 : 1
AT-20	120 / 208 / 240 / 277	105-305	2000	1900	1.5 +/- 0.5	4 : 1
AT-30	120	105-130	3000	2900	1.5 +/- 0.5	4 : 1
AT-368	240	185-305	3000	2900	1.5 +/- 0.5	4 : 1
AT-39	480	420-530	3000	2900	1.5 +/- 0.5	4 : 1

Switch	SPST Thermal Bi-Metallic
Fail Mode	On (Contacts normally closed)
Power Consumption	0.9 Watts (avg) @ 120 volts
Switch Lifetime	Exceeds 5,000 on/off operations
Temperature Range	-40°C to +65°C @ 96% RH
Housing	Die-Cast Aluminum, with UV resistant acrylic window.
Lead Wires	6", #10 AWG, Rated 105°C. (Models AT-30, 368 & 39) 6", #14 AWG, Rated 105°C. (All other models)
Nipple	1/2" Pipe
Nut	1/2" Pipe, zinc die-cast
Light Sensor	Cadmium Sulfide (Cds) Cell



**Area Lighting
Research, Inc.**

60 Asbury Road, Hackettstown, NJ 07840
800-257-3948 • 908-852-2205 • 908-852-2816 (fax)
e-mail: alrsales@alrmail.com
website: www.alrweb.com

*Proudly Serving the Electrical Industry
for Over 45 Years!*