



HEAVY-DUTY


HIGH PERFORMANCE SUPER SAWZALL® BLADES

MATRIX II HIGH SPEED STEEL TEETH WITH 8% COBALT. TOUGH BI-METAL DESIGN FOR THE FASTEST CUTTING, LONGEST BLADE LIFE AVAILABLE. 1/2" UNIVERSAL TANG.

TEETH RECOMMENDATIONS

See "RECOMMENDED FOR CUTTING" for proper blade selection

T.P.I.	STOCK THICKNESS	T.P.I.	STOCK THICKNESS	T.P.I.	STOCK THICKNESS
4/6	For cutting stock 1/2" and above	8/12	For cutting stock 1/4" thru 3/8"	14	For cutting stock 3/16" thru 1/4"
5/8 • 6 • 7	For cutting stock 3/8" and above	10		18	For cutting stock 1/8" thru 3/16"
		10/14		24	For cutting stock below 1/8"



THE AX™ AND THE TORCH® DEMOLITION BLADES

- 1/2" UNIVERSAL BLADE TANG FITS IN ALL SAWZALLS®
- BI-METAL CONSTRUCTION INCREASES BLADE LIFE. BLADES DO NOT SHATTER
- MATRIX II TEETH WITH 8% COBALT.
- UNIFORM GULLET DEPTH
- BLADE REVERSIBLE IN CLAMP

EXCLUSIVE "THE AX" FEATURES

- .062" THICK FOR STIFFER PERFORMANCE
- SLOPED SHAPE IDEAL FOR PLUNGE CUTTING
- STRENGTHENED TOOTH TIP
- WIDE GULLET SHAPE ALLOWS CHIPS TO CLEAR THE CUT

EXCLUSIVE "THE TORCH" FEATURES

- .042" AND .062" THICK* FOR STIFFER PERFORMANCE AND LONGER LIFE
- MORE AGGRESSIVE BLADE REMOVES MORE MATERIAL PER STROKE FOR FASTER CUTTING.

TRI-LINGUAL NO. 5 PER POUCH	CAT. NO. 25 PER BOX	CAT NO. 100 PER BOX	TEETH PER INCH	LENGTH x WIDTH x THICKNESS	RECOMMENDED FOR CUTTING:
					WOOD, NAIL EMBEDDED WOOD AND DEMOLITION
48-00-5021	48-00-8021	48-01-7021	5/8	6 x 1.0 x .062	Excellent for plunge cutting into wood and nail embedded wood without bending blades.
48-00-5026	48-00-8026	48-01-7026	5/8	9 x 1.0 x .062	Cut into walls that contain wood, nails, plaster and aluminum. Great for demolition work.
48-00-5027	48-00-8027	—	5/8	12 x 1.0 x .062	Extra long demolition blade.
					DEMOLITION, RESCUE AND REMODELING
NEW 48-00-5700	—	—	8	6 x 1.0 x .062	Metal pipe, channels, tubing, angle iron up to 4", steel, nail-embedded wood.
NEW 48-00-5705	—	—	8	9 x 1.0 x .062	
NEW 48-00-5710	—	—	8	12 x 1.0 x .062	
48-00-5712	48-00-8712	—	10	6 x 1.0 x .042	
48-00-5713	48-00-8713	—	10	9 x 1.0 x .042	
48-00-5782	48-00-8782	48-01-7782	14	6 x 1.0 x .042	
48-00-5787	48-00-8787	—	14	9 x 1.0 x .042	
48-00-5784	48-00-8784	48-01-7784	18	6 x 1.0 x .042	
48-00-5788	48-00-8788	—	18	9 x 1.0 x .042	
48-00-5789	48-00-8789	—	18	12 x 1.0 x .042	
					DEMOLITION, RESCUE AND REMODELING
NEW 48-00-5795	NEW 48-00-8795	—	14	9 x 1.0 x .062	Metal pipe, channels, tubing, angle iron up to 4", steel, nail-embedded wood. Also ideal for plunge cutting in rescue and demolition work.
NEW 48-00-5798	NEW 48-00-8798	—	18	9 x 1.0 x .062	
20mm					DEMOLITION, RESCUE AND REMODELING
48-00-5500 *	—	—	8	5.5 x 1.0 x .062	Metal pipe, channels, tubing, angle iron up to 4", steel, nail-embedded wood.
48-00-5510 *	—	—	8	9 x 1.0 x .062	
48-00-5515 *	—	—	8	12 x 1.0 x .062	
48-00-5512 *	—	—	10	6 x 1.0 x .042	
48-00-5513 *	—	—	10	9 x 1.0 x .042	
48-00-5582 *	—	—	14	6 x 1.0 x .042	
48-00-5587 *	—	—	14	9 x 1.0 x .042	
48-00-5570 *	—	—	14	12 x 1.0 x .042	

* Note: When using 20mm TORCH blades on Super Sawzalls with keyless blade clamp, operator must convert tool to Blade clamp 49-22-5004. For keyed blade clamp Super Sawzalls, convert to 49-22-5000 Blade Clamp.