Product specifications

# Eaton C14G4

## Catalog Number: C14G4

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 4 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder

### General specifications

**Product Name**
Eaton Bussmann series low voltage cylindrical fuse

**Catalog Number**
C14G4

**UPC**
051712754330

**EAN**
5027590494052

**Product Length/Depth**
51 mm

**Product Height**
14.3 mm

**Product Width**
14.3 mm

**Product Weight**
20.3 g

**Warranty**
1 year limited

**Compliances**
CE Marked GoST-R RoHS Compliant

**Certifications**
IEC 60269

## Product specifications

### Fuse indicator
Other

### Construction size
14 mm x 51 mm

### Rated voltage AC
690 V

### Connection
Ferrule end x ferrule end

### Quantity
10

### Suitable for
CH14 Modular fuse holder

### Material
Ceramic

### Mounting method
14 x 51 mm CH Modular fuse holder

### Release characteristic
Other

### Amperage Rating
4 A

### Frequency rating - max
62 Hz

### Utilization category
gL/gG (cable protection/equipment protection)

### Watt losses
1 W

### Fuse type
C14G

### Type
fuse

### Fuse shape
Cylindrical

### Breaking capacity
80 kA

### Fuse size

## Resources

### Catalogs
Product overview for machinery

Bussmann series complete full line catalog no. 1007

### Compliance information
UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

### Specifications and datasheets
Eaton Specification Sheet - C14G4

### Technical data sheets
720115 Cylindrical fuses

14 x 51 mm

### Frequency rating - min

45 Hz

### Class

Class C gL/gG

### Voltage rating

690 V

### Application

for industrial applications

for general purpose use

### Voltage type

AC

---

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia