


BURNDY Catalog Number
FQN10M25X03D
UPC Number
7818102930411
Description
MALEDISC 12-10AWG-FI NYL
Status
Active
Web Use
BURNDY Product Line
Dimensional

Width (in)	0.25
Strip Length	3/8"
Length (in)	1.50
F - Spacing (in) (Width - Center to Center)	0.13
Thickness	0.03
Diameter (in) - Total	0.96

Electrical

Max Voltage Rating	300
--------------------	-----

General

Product Description	Fully Insulated Brass Male Disconnect, 12-10 AWG, Nylon Insulated, Funnel Entry, Tin Plated
---------------------	---

Other

Bulk Package	FQN10M25X03B
--------------	--------------

Physical

Type of Plating	Tin
Connector Type	Male Disconnect
Insulation Type	Nylon
Plated (Yes or No)	Y

Approvals / Certifications

UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	Y
Industry Standards	UL467

Conductor(s)

Copper Solid Size (Range)	N/A
Copper Stranded (Range)	12 AWG-10 AWG

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175