

# Mini-Com® TX6A™ 10Gig UTP Jack Modules with MaTriX Technology

## SPECIFICATIONS

Category 6A/Class E<sub>A</sub>, 8-position, UTP jack module shall terminate 4-pair, 22 AWG - 26 AWG 100 ohm unshielded twisted pair cable and shall not require a punchdown tool. The termination cap shall be color coded blue to designate. Category 6A performance and shall include a universal label coded for T568A and T568B wiring schemes. The Mini-Com TX6A 10Gig UTP Jack Module must be installed as part of the TX6A 10Gig UTP Copper Cabling System to achieve IEEE 10GBASE-T certified performance.



## TECHNICAL INFORMATION

<b>Category 6A/Class E<sub>A</sub> channel and component performance:</b>	Certified channel performance in a 4-connector configuration up to 100 meters and exceeds the requirements of ANSI/TIA-568.2-D Category 6A and ISO 11801 Class E <sub>A</sub> Standards swept up to 650 MHz for supporting 10GBASE-T transmission over twisted-pair cabling systems as part of the TX6A 10Gig UTP Copper Cabling System  Exceeds component requirements of ANSI/TIA-568.2-D Category 6A and ISO 11801 Class E <sub>A</sub> Standards for supporting 10GBASE-T transmission over twisted-pair cabling systems
<b>FCC and ANSI compliance:</b>	Meets ANSI/TIA-1096-A contacts plated with 50 microinches of gold for superior performance
<b>IEC compliance:</b>	Meets IEC 60603-7 and IEC 60512-99-002
<b>RoHS compliance:</b>	Compliant
<b>PoE &amp; PoH compliance:</b>	Meets IEEE 802.3af / 802.3at and 802.3bt type 3 and type 4. Supports Power over HDBaseT up to 100 watts
<b>c(UL)us Listed:</b>	UL 1863 (Use as communications circuit accessory); CSA standard C22.2 UL 2043 (Suitable for use in air-handling spaces)
<b>Conductor termination range:</b>	Wire cap compatible with 22 AWG - 26 AWG solid or stranded cable with conductor insulation diameters of 0.06 in. (1.5mm) max and overall cable O.D. 0.2 in. - 0.33 in. (5.1mm - 8.4mm)
<b>Operating Temperature:</b>	14°F to 167°F (-10°C to 75°C)

## KEY FEATURES AND BENEFITS

<b>Interoperable:</b>	Compatible with components of the TX6A 10Gig UTP Copper Cabling System with MaTriX Technology for increased design flexibility
<b>Alien crosstalk suppression:</b>	Innovative MaTriX split foil technology provides superior alien crosstalk performance enabling high density applications
<b>100% performance tested:</b>	Confidence that each jack module will deliver the critical electrical performance requirements
<b>Individually serialized:</b>	Marked with quality control number for future traceability
<b>Shuttered version available:</b>	Integrated spring shuttered door keeps out dust and debris of unmated RJ45 jack modules automatically

## APPLICATIONS

Mini-Com TX6A 10Gig UTP Jack Modules are a component of the TX6A 10Gig UTP Copper Cabling System with MaTriX Technology. This end-to-end system provides a cost effective medium for ensuring that network bandwidth needs are easily met today and in the future. This solution helps ensure organizations efficiently and reliably meet their data transmission needs. With certified performance to the ISO 11801 Class E<sub>A</sub>, IEEE 802.3an-2006 and ANSI/TIA-568.2-D Category 6A Standards, this system will support high bandwidth applications like 10GBASE-T and HDBaseT and is ideal for running next generation Power over Ethernet (POE++).

### Mini-Com TX6A 10Gig UTP Jack Modules with Split Foil MaTriX Technology

<b>Jack module:</b>	CJ6X88TG*
<b>Shuttered jack module:</b>	CJH6X88TG*
<b>Up/Down 45° angle jack module:</b>	CJUD6X88TG*
<b>Left/Right 45° angle jack module:</b>	CJLR6X88TG*

### Tools and Accessories

<b>Jack module termination tool:</b>	TGJT or EGJT-1
<b>Wire snipping tool:</b>	CWST
<b>Wire stripping tool:</b>	CJAST
<b>Clear dust cap:</b>	MDC-C
<b>Blockout device:</b>	PSL-DCJB^^^+
<b>Phone icons:</b>	CIPIW-C
<b>Data icons:</b>	CID++-C
<b>Wire cap replacement, pack of 100:</b>	CJ6XCAPBU-X

\*Colors: IW (Off White), WH (White), EI (Electric Ivory), IG (International Gray), AW (Arctic White), BL (Black), BU (Blue), RD (Red), YL (Yellow), GR (Green), OR (Orange) or VL (Violet)

^^^Colors other than Red: - BL (Black), -BU (Blue), -YL (Yellow), -GR (Green), -OR (Orange), -IW (Off White), or -IG (International Gray)

+Add -C to indicate 100 pieces per bulk pack to reduce single-use plastic

++Colors: WH (White), BU (Blue), RD (Red), YL (Yellow), GR (Green), OR (Orange)  
-X indicates bulk packages of 10 pieces per pack to reduce single-use plastic

Contact customer service for bulk-packaged and/or keyed jack modules.

# Mini-Com® TX6A™ 10Gig UTP Jack Modules with MaTriX Technology


## ADDITIONAL SPECIFICATIONS

Mechanical Test		Test Method	Measurement	Typical Test Results
Normal Force		ANSI/TIA-1096-A	Load (grams)	> 100
Vibration		IEC 512-6d	Circuit Resistance (mOhms)	< 40
Shock		IEC 512-6c	Contact Disturbance (microsecond)	< 5
Durability		IEC 512-6a	Circuit Resistance (mOhms)	< 20
Mating/Un-mating	IEC 512-6b	Mating Force (N)		
		Un-mating Force (N)		
Termination Cycles		IEC 352	Number of Cycles	> 20
Mating Cycles		IEC 60603-7	Number of Plug Insertions	> 2500

Electrical Test		Test Method	Measurement	Typical Test Results
Low Level Circuit Resistance		IEC 512-2a	Resistance (mOhms)	< 20
Dielectric Withstand Voltage		IEC 512-4a	1000 VAC, 1 minute	Passed
Insulation Resistance		IEC 512-3a	Resistance (MOhms)	> 500

Environmental Test		Test Method	Measurement	Typical Test Results
Temperature Life		IEC 512-9b	Circuit Resistance (mOhms)	< 40
Humidity		IEC 512-11c		
Thermal Shock		IEC 512-11d		
Climatic Sequence		IEC 512-11a		
Flowing Mixed Gas Corrosion		IEC 512-11g		

## ENGINEERING DRAWINGS



Dimensions are in inches. [Dimensions in brackets are metric].

### WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA Phone: 800.777.3300	PANDUIT EUROPE LTD. London, UK Phone: 44.20.8601.7200	PANDUIT SINGAPORE PTE. LTD. Republic of Singapore Phone: 65.6305.7575	PANDUIT JAPAN Tokyo, Japan Phone: 81.3.6863.6000	PANDUIT LATIN AMERICA Guadalajara, Mexico Phone: 52.33.3777.6000	PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia Phone: 61.3.9794.9020
------------------------------------------	-------------------------------------------------------------	-----------------------------------------------------------------------------	--------------------------------------------------------	------------------------------------------------------------------------	-----------------------------------------------------------------------------

For a copy of Panduit product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)



For more information  
Visit us at [www.panduit.com](http://www.panduit.com)  
Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)  
or by phone: 800.777.3300

© 2024 Panduit Corp.  
ALL RIGHTS RESERVED.  
COSP231-WW-ENG  
7/2024