

Non-Insulated Stranded Conductor for Lightning Protection – LPA100250



- Provides a path to ground for lightning currents



Part Number	LPA100250
Certification Details	UL® 96
Material	Aluminum
UL Conductor Class	Class I
Conductor Type	Smooth Weave
Number of Wires	25
Wire Diameter	0.064"
Diameter	1/2"
Length	250'
Cross Section	98.64 kcmil
Unit Weight	0.102 lb
Certifications	cULus
Standard Packaging Quantity	250'
UPC	78285661316

Equivalent Conductor Size	
Part Number	Conductor Size
LPC134xxx	2/0
LPC136xxx	3/0
LPC137xxx	4/0

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.