

NEER™ Zinc Offset Nipples and Three Piece Couplings

NEC/CEC:
Listed for Ordinary Locations

NEC:
Listed for Ordinary Locations

RN: 3/4" Offset

Applications

- To provide an offset connection between two outlet boxes or enclosures.

Material/Finish

- Zinc diecast

NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E32539
- CSA Standard: C22.2 No. 18.3
- CSA Certified: 70872
- NEMA: FB-1



RN-50

TPC: Three Piece

Applications

- Provides threaded coupling between lengths of rigid conduit and IMC conduit elbows, where neither can be rotated.

Material/Finish

- Malleable iron/zinc plated


NEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E163167
- NEMA: FB-1



TPC - 50

Illustrated Dimensions



| Trade Size (Inches) | Dimensions in Millimeters (Inches) | | | Catalog Number |
|---------------------|------------------------------------|------------------|--|----------------|
| | Body Length | Maximum Diameter | | |
| 1/2 | 62.2 (2.45) | 23.9 (0.94) | | RN-50 |
| 3/4 | 66.0 (2.60) | 29.2 (1.15) | | RN-75 |
| 1 | 70.1 (2.76) | 35.6 (1.40) | | RN-100 |
| 1-1/4 | 73.7 (2.90) | 46.7 (1.84) | | RN-125 |
| 1-1/2 | 77.5 (3.05) | 52.3 (2.06) | | RN-150 |
| 2 | 82.0 (3.23) | 67.6 (2.66) | | RN-200 |

| Trade Size (Inches) | Dimensions in Millimeters (Inches) | | | Catalog Number |
|---------------------|------------------------------------|--------------|--------------|----------------|
| | A | B | C | |
| 1/2 | 34.5 (1.36) | 33.0 (1.30) | 30.5 (1.20) | TPC-50 |
| 3/4 | 41.4 (1.63) | 39.9 (1.57) | 33.0 (1.30) | TPC-75 |
| 1 | 43.2 (1.70) | 54.1 (2.13) | 47.8 (1.88) | TPC-100 |
| 1-1/4 | 53.8 (2.12) | 62.0 (2.44) | 54.4 (2.14) | TPC-125 |
| 1-1/2 | 50.8 (2.00) | 73.4 (2.89) | 66.3 (2.61) | TPC-150 |
| 2 | 60.5 (2.38) | 86.6 (3.41) | 79.5 (3.13) | TPC-200 |
| 2 - 1/2 | 64.5 (2.54) | 102.4 (4.03) | 99.3 (3.91) | TPC-250 |
| 3 | 65.0 (2.56) | 16.8 (4.60) | 110.7 (4.36) | TPC-300 |
| 3 - 1/2 | 64.5 (2.54) | 17.1 (4.61) | 111.0 (4.37) | TPC-350 |
| 4 | 100.1 (3.94) | 42.5 (5.61) | 129.5 (5.10) | TPC-400 |