

Eaton 200FM

Catalog Number: 200FM

Eaton Bussmann series high speed British standard fuse, 240 Vac, 150 Vdc, 200A, 200 kAIC, None, Fuse, Blade end X blade end, Stud - 200FM

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed British standard fuse	200FM
	UPC
	051712832199
EAN	Product Length/Depth
5027590036993	112 mm
Product Height	Product Width
39 mm	39 mm
Product Weight	Warranty
226 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	IEC Rated UL Recognized Designed and tested to BS88 part 4 IEC 60269-4 UL recognized CCC



Electrical data

Amperage Rating

200 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

450 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 450 Vdc (IEC), 50 kA at 500 Vdc (UL)

Class

Class aR

Pre arc (I2T)

2600

Clearing (I2T)

10500

Watt losses

40 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Certification reports

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Compliance information

[UKCA Low voltage fuse-links *AET,*AEET,*AFEE etc](#)

Specifications and datasheets

[Eaton Specification Sheet - 200FM](#)

Technical data sheets

[720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)