


## Wire-Nut® Wire Connectors

- Positive grip shell design provides fast, easy installation
- Square-wire fixed spring design creates its own threads for a grip that will last
- Deep, wide skirt protects against arcing and flash-over
- Reusable for easy circuit changes
- Tough, UL94V-2 flame retardant shell rated at 105°C (221°F)



Model	Color	Wire Combination Range	Wire Combination Range (mm)	Quantity	Cat. No.
71B®	Gray	300V 22 to 16 AWG Min. 2 #22 – Max. 2 #16	300V ,34mm <sup>2</sup> to 1,5mm <sup>2</sup> Min. 2- ,34mm <sup>2</sup> Max. 3-1,5mm <sup>2</sup>	Box of 100	30-071
				Carton of 1,000	30-171
				Keg of 25,000	30-271
				Barrel of 150,000	30-871
				Box of 100	30-072
72B®	Blue	300V 22 to 14 AWG Min. 2 #22 – Max. 3 #16	300V ,34mm <sup>2</sup> to 2,5mm <sup>2</sup> Min. 2- ,34mm <sup>2</sup> Max. 3-1,5mm <sup>2</sup>	Carton of 1,000	30-172
				Keg of 10,000	30-272
				Barrel of 85,000	30-872
				Box of 100	30-073
				Jar of 300	30-073J
73B®	Orange	600V* 22 to 14 AWG Min. 1 #18 & 1 #20 Max. 2 #14	600V* ,34mm <sup>2</sup> to 2,5mm <sup>2</sup> Min. 1- ,75mm <sup>2</sup> w/1- ,50mm <sup>2</sup> Max. 4-1,5mm <sup>2</sup> w/1- ,50mm <sup>2</sup>	Bag of 500	30-273
				Carton of 1,000	30-173
				Keg of 10,000	30-673
				Barrel of 50,000	30-873
				Box of 100	30-074
74B®	Yellow	600V* 18 to 12 AWG Min. 2 #18 Max. 4 #14 & 1 #18	600V* ,75mm <sup>2</sup> to 4,0mm <sup>2</sup> Min. 2- ,75mm <sup>2</sup> Max. 4-2,5mm <sup>2</sup> w/1- ,75mm <sup>2</sup>	Jar of 175	30-074J
				Bag of 500	30-274
				Carton of 1,000	30-174
				Keg of 5,000	30-674
				Barrel of 35,000	30-874
76B®	Red	600V* 18 to 6 AWG Min. 2 #14 Max. 5 #12	600V* ,75mm <sup>2</sup> to 16,0mm <sup>2</sup> Min. 2- 2,5mm <sup>2</sup> Max. 2- 4,0mm <sup>2</sup>	Box of 100	30-076
				Jar of 150	30-076J
				Bag of 250	30-276
				Carton of 1,000	30-176
				Barrel of 15,000	30-876

\*1,000V maximum in fixtures and signs

## High-Temp Wire-Nut® Wire Connectors

All of the same features as the Wire-Nut® Wire Connector, plus:

- Black, thermoplastic shell designed to withstand extreme heat build-up found in high-wattage light fixtures and signs
- UL Listed to 150°C (302°F)



Model	Color	Wire Combination Range	Wire Combination Range (mm)	Quantity	Cat. No.
71B®	Black	300V 22 to 16 AWG Min. 2 #22 Str – Max. 2 #16	300V ,34mm <sup>2</sup> to 1,5mm <sup>2</sup> Min. 2- ,34mm <sup>2</sup> – Max. 2-1,5mm <sup>2</sup>	Box of 100	30-3627
				Carton of 1,000	30-151
				Keg of 25,000	30-251
72B®	Black	300V 22 to 14 AWG Min. 2 #22 – Max. 3 #16	300V ,34mm <sup>2</sup> to 2,5mm <sup>2</sup> Min. 2- ,34mm <sup>2</sup> – Max. 3-1,5mm <sup>2</sup>	Box of 100	30-3628
				Carton of 1,000	30-152
				Keg of 10,000	30-252
73B®	Black	600V* 22 to 14 AWG Min. 1 #18 w/1 #20 Max. 2 #14	600V* ,34mm <sup>2</sup> to 2,5mm <sup>2</sup> Min. 1- ,75mm <sup>2</sup> w/1- ,50mm <sup>2</sup> Max. 4-1,5mm <sup>2</sup> w/1- ,50mm <sup>2</sup>	Box of 100	30-3629
				Carton of 1,000	30-153
				Keg of 10,000	30-253
59B™	Black	600V* 22 to 12 AWG Min. 2 #20 – Max. 3 #14	600V* ,34mm <sup>2</sup> to 4,0mm <sup>2</sup> Min. 2- ,5mm <sup>2</sup> – Max. 3-2,5mm <sup>2</sup>	Box of 100	30-059
				Keg of 5,000	30-259

\*1,000V maximum in fixtures and signs