

e-Vision Low Wattage 20-150W

E-VISION ELE MH BAL 20W M175 120V

Low frequency electronic HID ballasts such as the Philips Advance e-Vision line constantly measure and adjust the wattage, optimizing delivery of the ceramic lamps' superior color properties. This makes ceramic metal halide operated by e-Vision ballasts the premier choice for many applications previously illuminated by either tungsten halogen or incandescent sources, such as retail lighting.

Product data


General Information		Input Power (Nom) 26 W	
ANSI Code	C175	Rated Lamp Watts	22 W
Lamp Type	22W Philips Mini MC	Wiring	
Number of Lamps	1 piece/unit	Color Input Terminals	No terminals
Ballast Type	Electronic HID	Color Output Terminals	No terminals
Base Model	RMH20KLF	Wire Striplength	0.50 mm
Suitable For Outdoor Use	Yes	Control Wire Gauge	NA
Operating and Electrical		Wire Length By Color	All leads = 6"
Input Voltage	120 V	Wire Gauge (Nom)	18AWG mm
Input Frequency	50 to 60 Hz	Wire Type	Stranded
Max THD	15 %	Remote Wiring Configuration Allowed	Yes
Lamp Current Crest Factor (Nom)	1.8	Tandem Wiring Configuration Allowed	No
Ignition Time (Nom)	1200 s	Through Wiring Configuration Allowed	No
Ballast Factor (Nom)	1	Connector Type	No connector
Power Factor (Nom)	0.90		
Input Current (Operating) (Max)	0.23 A		
Input Current (Operating) (Min)	0.23 A		

e-Vision Low Wattage 20-150W

Temperature	
T-Case Maximum (Nom)	90 °C
Mechanical and Housing	
Housing Material	Metal
Housing	K
Housing Dimensions	4.1" x 1.3" x 1.2"
Approval and Application	
EMC Immunity Standard	FCC Non-Consumer
Approbation Marks	CSA certificate UL certificate RoHS Compliant
Sound Rating	A

UL Recognized	No
Product Data	
Order product name	E-VISION RMH20KLFM
EAN/UPC - Product	781087057360
Order code	RMH20KLFM
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700615588
Net Weight (Piece)	168.000 g

Dimensional drawing



E-VISION RMH20KLFM

Product	A1	A2	A3	B1	B2	C1
---------	----	----	----	----	----	----

