## Hubbell SystemOne Through-Floor Fitting



Step down installation clips allow the ÛWWLQJ WR EH LQVWDOOHG GLUHFWO\ XQGHU FRQFUHWH ÜRRU DERYH

%DUULHU H[SDQGV GXULQJ ÛUH FRQGLWLRQV PDLQWDLQ WKH ÜRRUpV ÛUH UDWLQJ

$GMXVWDEOH ORZHU ÛUH EDUULHU DFFRPPRGDWHV FRQFUHWH ÜRRU WKLFNQHVVHV JUHDWHU WKDQ

)HDWXUHV GXDO (07 FRQGXLW WXEHV IRU increased cable capacity.


„ Accepts all Hubbell SystemOne covers and sub-plates (4X4 FRPSRQHQW VRO[ FRQVWUXFWLRQ IRU ERWK FRQFUHWH DQG ZRRG IORRUV

„ Brings power, voice, data and multimedia precisely where needed.

„ Installs in 4" core hole.

„ 8/ OLVWHG IRU XVH LQ KU ÛU

## Hubbell SystemOne Universal Cover



+LQJHG GRRUV RSHQ GHJUHHV ÜXVK WR WKH FDUSHW ÜDQJH RU WLOH

Screws allow each door to be secured independently.

8QLYHUVDO FDUSHW RU WLOH ÜDQJH FDQ EH XVHG for Hubbell SystemOne Fire-Rated Poke-Through or PVC Floor Box.

„ Cast aluminum construction available in durable black, gray, brass, aluminum and LYRU\ SRZGHU FRDW ÛQLVKHV

„ )HDWXUHV 6FUXE6KLHOGw WHFK exceeds UL514A and UL514C scrub water exclusion requirements.

„ Provides consistent look and maximum functionality throughout.

## Hubbell SystemOne Sub-plates

:KLOH QR RQH FDQ SUHGLFW WKH IXWXUH design allows users to economically upgrade Hubbell SystemOne FRPTs to accommodate future moves, adds and changes.



„ +XEEHOO ,QFRUS $9 UHF and four openings for voice/data jacks and multimedia connectors.

„ +XEEHOO ,1),1H67$7,21w IURQW modular connectivity.

„ $FFRPPRGDWHV ([WURQ (OHFWU $UFKLWHFWXUDO 6HULHVw DXGL integration products.

„ Ortronics fi 6LHPRQw fi 3DQ67,DW ; and keystone options enable maximum data ÜH[LELOLW\

„ Large capacity and multi-service furniture feed applications.

„ GFCI, surge and standard Style Line receptacles.

„ Twist-Lock fi receptacle with or without data jacks.