



Representative Image

**Catalog No. TH3221****Description: 30A 2P HD N1 240V FUSIBLE SWITCH****UPC No 783164008951****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH328951

**Descriptors**

Category	Heavy Duty
GO Schedule	S1

**Specifications**

Voltage	240 AC
Amperage	30 A
Poles	2
Wires	3
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Options	None
Wire Range (Cu/Al)	14-8 CU;12-8 AL
240 Vac, NEC Std, 1-ph	1.5 hp
240 Vac, Time Delay, 1-ph	3.0 hp
250 Vdc	5.0 hp
GSA Compliance	Yes

**Classifications**

CSA Certified	Yes
UL Listed	Yes

**Dimensions**

Height	10.3 in
Depth	3.3 in
Width	6.3 in
Weight	6.0 lb

## Publications

Title	Publication No.	Publication Type
<a href="#">60A - Safety Switches</a> 1 page outline drawing in .pdf format.	10103091-SH102	Drawings-Outline and Dimensional

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.