

**PHILIPS****Lighting**

# U-Bent Rapid Start T8

## FB29T8/TL835/EW/ALTO 15/1

Philips leads the industry with the lowest level mercury technology. Reducing the mercury level (source reduction) during the manufacturing phase is essential to creating products that are less harmful to the environment.


### Product data

General Information		Nominal Length (Inch)	22.44
Base	G13 [ Medium Bi-Pin Fluorescent]		
Life 3-Hr Start [Hrs]	24000 h		
Features	ALTO® (ALTO)		
Light Technical			
Color Code	TL835 [ CCT of 3500K (835)]		
Initial lumen (Nom)	2550 lm		
Design Mean Lumens	2300 lm		
Correlated Color Temperature (Nom)	4100 K		
Color Rendering Index (Nom)	85		
Operating and Electrical			
Power (Rated) (Nom)	29 W		
Mechanical and Housing			
Cap-Base Information	Green Base		
Approval and Application			
Energy Saving Product	Energy Saving		
Mercury (Hg) Content (Nom)	3.0 mg		
Product Data			
XUCDM.COPY.Product.Title	FB29T8/TL835/EW/ALTO 15/1		
EAN/UPC - Product	04667226763		
Order code	226761		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	15		
Material Nr. (12NC)	927861383502		
Net Weight (Piece)	0.001 kg		

### Warnings and Safety

## U-Bent Rapid Start T8

### Dimensional drawing



#### Product

FB29T8/TL835/EW/ALTO 15/1

FB29T8/TL835 EW ALTO® ES

