Hubbell SystemOne Through-Floor Fitting

Step down installation clips allow the ÛWWLQJ WR EH LQVWDOOHG sub-plates (4X4 FRPT system uses a separate ÛRRU DERYH

%DUULHU H[SDQGV GXULQJ ÛRHFHOOHQW LVRODWLRQ IRU ERW PDLQWDLQ WKH ÛRRUpV ÛUHUDWLRQJ

$GMXVWDEOH ORZHU ÛUH EDUULHU DFFRPPRGDWHV FRQFUHWH ÛRRU WKLFNQHVVHVIURP WR

)HDWXUHV GXDO (07 FRQGXLW WXEHV IRU increased cable capacity.

- » Accepts all Hubbell SystemOne covers and sub-plates (4X4 FRPT system uses a separate FRPT and sub-plate).

- » ([FHOOHQW LVRODWLRQ IRU ERW construction.

- » Brings power, voice, data and multimedia precisely where needed.

- » Installs in 4" core hole.

- » 8/ OLVWHG IRU XVH LQ KU Û

Hubbell SystemOne Universal Cover

+LQJHG GRRUV RSHQ GHJUHHV ÛXVK WR WKH FDUSHW ÛDQJH RU WLOH

Screws allow each door to be secured independently.

8QLYHUVDO FDUSHW RU WLOH ÛDQJH FDQ EH XVHG for Hubbell SystemOne Fire-Rated Poke-Through or PVC Floor Box.

- » Cast aluminum construction available in durable black, gray, brass, aluminum and LYRU\ SRZGHU FRDW ÛQLVKHV

- »)HDWXUH 6FUXE6KLHOGw WHFK exceeds UL514A and UL514C scrub water exclusion requirements.

- » Provides consistent look and maximum functionality throughout.

Hubbell SystemOne Sub-plates

:KLOH QR RQH FDQ SUHGLFW WKH IXWXUH design allows users to economically upgrade Hubbell SystemOne FRPTs to accommodate future moves, adds and changes.

- » +XEEHOO ;R IRXU VDE SODWHV SURYLGH and four openings for voice/data jacks and multimedia connectors.

- » +XEEHOO ,1),1H67$7,21w IURQW modular connectivity.

- » $FFRPPRGDWHV ([WURQ (OHFWU $UFKLWHFWXUDO 6HULHVw DXGL integration products.

- » Ortronics 6LHPRQw 3DQ6;,1; and keystone options enable maximum data ÛH[LELOLW\

- » Large capacity and multi-service furniture feed applications.

- » GFCI, surge and standard Style Line receptacles.

- » Twist-Lock receptacle with or without data jacks.