


## Polypro General Purpose Rope



- Not for cable pulling. See the ropes listed with cable pullers for recommended cable pulling ropes.
- Highly visible bright yellow with green runner, excellent for roping off areas on construction sites. Handy reel for dispensing.
- Rot and mildew resistant.
- Weather resistant.
- Economical general purpose rope.



| Rope Diameter            | Rope Length |        | Cat./UPC No. | Average Breaking Strength |         | Weight |      |
|--------------------------|-------------|--------|--------------|---------------------------|---------|--------|------|
|                          |             |        |              |                           |         | lbs.   | kg.  |
| <b>3/16"</b><br>(4.8 mm) | 250'        | 76 m   | 408 / 21467  | 720 lbs.                  | 3.2 kN  | 3      | 1.4  |
|                          | 600'        | 182 m  | 409 / 21468  | 720 lbs.                  | 3.2 kN  | 6      | 2.7  |
|                          | 1,000'      | 304 m  | 410 / 21469  | 720 lbs.                  | 3.2 kN  | 9      | 4.1  |
|                          | 5,000'      | 1524 m | 411 / 21470  | 720 lbs.                  | 3.2 kN  | 41     | 18.6 |
|                          | 10,000'     | 3048 m | 429 / 22507  | 720 lbs.                  | 3.2 kN  | 78     | 35.5 |
| <b>1/4"</b><br>(6.4 mm)  | 250'        | 76 m   | 412 / 21471  | 1130 lbs.                 | 5.0 kN  | 4      | 1.8  |
|                          | 600'        | 182 m  | 413 / 21472  | 1130 lbs.                 | 5.0 kN  | 9      | 4.1  |
|                          | 1,000'      | 304 m  | 414 / 21474  | 1130 lbs.                 | 5.0 kN  | 13     | 5.9  |
| <b>3/8"</b><br>(9.5 mm)  | 50'         | 15 m   | 415 / 21475  | 2430 lbs.                 | 10.8 kN | 3      | 1.4  |
|                          | 100'        | 30 m   | 416 / 21476  | 2430 lbs.                 | 10.8 kN | 4      | 1.8  |
|                          | 250'        | 76 m   | 417 / 21477  | 2430 lbs.                 | 10.8 kN | 9      | 4.1  |
|                          | 600'        | 182 m  | 418 / 21520  | 2430 lbs.                 | 10.8 kN | 19     | 8.6  |
|                          | 1,200'      | 365 m  | 425 / 22212  | 2430 lbs.                 | 10.8 kN | 39     | 17.7 |
| <b>1/2"</b><br>(12.7 mm) | 50'         | 15 m   | 419 / 21478  | 3780 lbs.                 | 16.8 kN | 4      | 1.8  |
|                          | 100'        | 30 m   | 420 / 21479  | 3780 lbs.                 | 16.8 kN | 6      | 2.7  |
|                          | 250'        | 76 m   | 421 / 21480  | 3780 lbs.                 | 16.8 kN | 15     | 6.8  |
|                          | 600'        | 182 m  | 422 / 21521  | 3780 lbs.                 | 16.8 kN | 35     | 15.9 |
|                          | 1,200'      | 365 m  | 426 / 22213  | 3780 lbs.                 | 16.8 kN | 66     | 29.9 |
| <b>5/8"</b><br>(15.9 mm) | 250'        | 76 m   | 423 / 21522  | 5580 lbs.                 | 24.8 kN | 26     | 11.8 |
|                          | 600'        | 182 m  | 424 / 21524  | 5580 lbs.                 | 24.8 kN | 55     | 24.9 |
|                          | 1,200'      | 365 m  | 427 / 22214  | 5580 lbs.                 | 24.8 kN | 100    | 45.5 |
| <b>3/4"</b><br>(19.1 mm) | 300'        | 91 m   | 680 / 15356  | 7650 lbs.                 | 34.0 kN | 39     | 17.7 |
|                          | 600'        | 182 m  | 688 / 18273  | 7650 lbs.                 | 34.0 kN | 74     | 33.6 |
|                          | 1,200'      | 365 m  | 428 / 22215  | 7650 lbs.                 | 34.0 kN | 143    | 64.9 |