

1731 & 1732 Portable C-Frame Punch Drivers

CAT. NO.	UPC NO.	DESCRIPTION	HOLE SIZE			KIT CAT/UPC.NO.				
			SIZE	PG	Ø mm	1731/ 15911	1731H767/ 20486	1731F1725/ 25169	1732/ 27361	1732H755/ 27362
		C-Frame with Ram				✓	✓	✓	✓	✓
13266	13266	Punch Adapter - 3/8" Ø x 1/2" (9.5 mm)							✓	✓
13267	13267	Punch Adapter - 3/4" Ø x 1" (19.0 mm)							✓	✓
13276	13276	Punch Adapter - 3/8" Ø x 1/2" (9.5 mm)				✓	✓	✓		
13277	13277	Punch Adapter - 3/4" Ø x 1" (19.0 mm)				✓	✓	✓		
13268	13268	Punch Adapter - 1-1/8" Ø (28.6 mm)							✓	✓
121AV	04006	1/2" Conduit Size Punch	1/2"	16	22.5	✓	✓	✓		
123AV	04008	3/4" Conduit Size Punch	3/4"	21	28.3	✓	✓	✓		
125AV	04010	1" Conduit Size Punch	1"	-	34.6	✓	✓	✓		
12087	12087	C-Frame 1/2" Conduit Size Die	1/2"	16	22.5	✓	✓	✓		
12086	12086	C-Frame 3/4" Conduit Size Die	3/4"	21	28.3	✓	✓	✓		
12085	12085	C-Frame 1" Conduit Size Die	1"	-	34.6	✓	✓	✓		
1725	25144	1725 Hydraulic Foot Pump						✓		
16634	16634	Steel Case				✓	✓	✓		
38316	38316	High Pressure Hose Unit - 1/4" x 3' (includes 1 each of the following 3 items:)					✓			
54169	54169	- 1/4" Male Coupler								
54170	54170	- Dust Cap								
06302	06302	- High Pressure Hose, 1/4" x 3'								
11791	11791	Die Adapter - 3/8" Ø (9.5 mm)							✓	✓
11790	11790	Die Adapter - 3/4" Ø (19.0 mm)							✓	✓
11789	11789	Die Adapter - 1-1/8" Ø (28.6 mm)							✓	✓
767	13284	Hydraulic Hand Pump					✓			
755	15677	Hydraulic Hand Pump								✓
37729	37729	Hydraulic Hose - 1/4" x 10' (3 m)						✓		
11289	11289	Hydraulic Hose - 3/8" x 6' (9.5 mm x 1.8)								✓
27335	27335	Metal Case							✓	✓
50642	50642	Nut - 3/4" - 10 (19.0 mm)							✓	✓
12079	12079	Frame								
15631	15631	Ram								
37614	37614	Quick Disconnect								
11903	11903	C-Frame								
13814	13814	Packing Kit								



1731 Portable C-Frame Punch Drivers



- Fast, one-shot punching, no predrilling of pilot holes.
- Great for punching junction boxes and small enclosures.
- Punch can be used with ram inside or outside of the junction box.
- Throat measures 8" (203 mm) deep.
- For use with 1/2" - 1" (22.5 mm - 34.6 mm) conduit size and accessory sizes only.

Cat. No.	UPC No.	Description	Weight	
			lbs.	kg.
1731	15911	Driver with ram, 1/2" through 1" conduit (22.5 mm through 34.6 mm) punches and dies	32	15
1731H767	20486	Same as 1731 with 767 hydraulic hand pump	36	17
1731F1725	25169	Same as 1731 with 1725 hydraulic foot pump	43	20
21316	21316	Pg-9 (15.2 mm) Punch (optional)		
18557	18557	Pg-9 (15.2 mm) Die (optional)		
17700	17700	Pg-11 (18.6 mm) Punch (optional)		
18558	18558	Pg-11 (18.6 mm) Die (optional)		
17697	17697	Pg-13 (20.4 mm) Punch (optional)		
18559	18559	Pg-13 (20.4 mm) Die (optional)		
36282	36282	1-7/32" (30.5 mm) Oil Tight Punch (optional)		
37103	37103	1-7/32" (30.5 mm) Oil Tight Die (optional)		

SPECIFICATIONS

Capacity:

Up through 10 gauge (3.0 mm) mild steel with Greenlee special C-Frame dies and standard punches; 1/2" through 1" conduit and 15.2 mm through 30.5 mm.

Cat. No.	UPC No.	Description	Hole Size			Kit Cat./UPC No.		
			Conduit & Pipe Size	Pg	ø mm	1731/15911	1731H767/20486	1731F1725/25169
		C-Frame with Ram				✓	✓	✓
13276	13276	Punch Adapter-3/8"ø x 1/2" (9.5 mmø)				✓	✓	✓
13277	13277	Punch Adapter-3/4"ø x 1" (19.0 mmø)				✓	✓	✓
121AV	04006	1/2" Conduit Size Punch	1/2"	16	22.5	✓	✓	✓
123AV	04008	3/4" Conduit Size Punch	3/4"	21	28.3	✓	✓	✓
125AV	04010	1" Conduit Size Punch	1"	-	34.6	✓	✓	✓
12087	12087	C-Frame 1/2" Conduit Size Die	1/2"	16	22.5	✓	✓	✓
12086	12086	C-Frame 3/4" Conduit Size Die	3/4"	21	28.3	✓	✓	✓
12085	12085	C-Frame 1" Conduit Size Die	1"	-	34.6	✓	✓	✓
16634	16634	Steel Case				✓	✓	✓
1725	25144	1725 Hydraulic Foot Pump						✓
37729	37729	Hydraulic Hose-1/4" x 10' (3 m)						✓
767	13284	Hydraulic Hand Pump					✓	
38316	38316	High Pressure Hose Unit-1/4" x 3' (includes 1 each of the following 3 items)					✓	
54169	54169	- 1/4" Male Coupler					✓	
54170	54170	- Dust Cap					✓	
06302	06302	- High Pressure Hose-1/4" x 3'					✓	