



# Switch Start Metal Halide Protected

## MP1000/BU 6PK

An efficient, protected "O" rated lighting solution that is suitable for open-rated fixtures. Ideal for both indoor and outdoor applications.

### Warnings and Safety

• R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)


### Product data

General Information	
Operating Position	H15 [Hanging +/-15D or Base Up (BU)]
Cap-Base	EX39 [Exclusionary Mogul Screw]
Light Technical	
Color Code	635 [CCT of 3500K]
Color Designation	White (WH)
Chromaticity Coordinate X (Nom)	405
Chromaticity Coordinate Y (Nom)	390
Correlated Color Temperature (Nom)	3500 K
Luminous Efficacy (rated) (Nom)	107 lm/W
Color rendering index (CRI)	65
Operating and Electrical	
Lamp Current (Nom)	4.1 A
Voltage (Nom)	263 V
Voltage (Nom)	
263 V	
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Hard Glass
Bulb Shape	BT56
Approval and Application	
Mercury (Hg) Content (Nom)	150 mg
Product Data	
Order product name	MP1000/BU 6PK
Order code	928601179601
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material number (12NC)	928601179601

## Switch Start Metal Halide Protected

Full product name	MP1000/BU 6PK
EAN/UPC - Case	50046677281187

### Dimensional drawing



Product	D	C (max)
MP1000/BU 6PK	7 inch	15.375 inch

