SIEMENS

Data sheet US2:52SC6GE

Keyed selector switch, metal Maintained G Cam 3 position Operator only Non-Illuminated Key type 501CH (standard) Key removalble in all positions UL file E22655 in Vol. 6 (7) Sec. 13 (2)

design of the product	Actuator round	
Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
design of the actuating element	Key-operated switch	
material of the actuating element	metal	
type of unlocking device	key unlatching	
number of switching positions	3	
switch position for key distraction	removable in every position	
lock make	ILLINOIS	
key number	501CH	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
color of the front ring	chrome	
Holder		
material of the holder	Metal	
General technical data		
product component		
• light source	No	
degree of pollution	1	
protection class IP	IP66	
operating frequency maximum	600 1/h	
Ambient conditions		
ambient temperature		
 during operation 	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Further information		

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6GE

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6GE

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6GE

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ EPLAN\ macros,\ ...)$

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6GE&lang=en

last modified: 5/31/2021

US2:5	280	SGE
Page 2		JGE