

COMPACT TDX PANEL PROTECTOR, 50 KA, 120/208 V UN

CATALOG NUMBER

TDX50C120/208



CERTIFICATIONS



FEATURES

Transient Discriminating (TD) Technology provides increased service life

Built-in features include TD Technology, thermal protection and short circuit current fusing

Compact NEMA®-4 enclosure design can be flush mounted or installed in a small space

LED status indication and voltage-free contacts provide remote status monitoring

50kA 8/20µs maximum surge rating provides protection suitable for sub-distribution panels and a long operational life

PRODUCT ATTRIBUTES

Nominal System Voltage (Un): 120/208 V

Distribution System: 3Ph 4W+G

Max Continuous Operating Voltage (Uc): 170/276 VAC

Stand-off Voltage: 240/415 VAC

Frequency: 50 – 60 Hz

Short Circuit Current Rating (SCCR): 200 kA

Nominal Discharge Current (In), IEC: 40 kA 8/20 µs

Nominal Discharge Current (In), UL: 10 kA 8/20 μ s

Max Discharge Current (Imax), Per Phase: 50 kA 8/20 μ s

Voltage Protection Rating (VPR), L-N: 600 V @ 3 kA;1,200 V @ 20 kA

Protection Modes: L-N;L-PE;N-PE

Remote Contacts: Yes

Status Indication: LED

Surge Counter: No

Technology: Over-current fusing;TD technology with thermal disconnect

Lead Size: #10

Lead Length: 30"

Temperature: -40 to 176 °F

Ground Lead Length: 36"

Enclosure Material: Metal

Enclosure Rating: IP 65;NEMA®-4

Mounting: 3/4" straight nipple

Width (W): 3.310"

Height (H): 6.020"


Depth (D): 3.070"

Unit Weight: 1.540 lb

Certification Details: UL® 1449 Edition 4 Type 1/2, 10 kA Mode

Complies With: ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C;ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 2, 50 kA 8/20 μ s;IEC® 61643-1 Class I, Class II

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.