3420 & 3450 Series Heavy-Duty Fan Forced Wall Heaters



Features

- Powder coated bar stock steel tamper proof grille, with extruded Aluminum frame & 16 gauge housing.
- In-Built double pole tamper proof thermostat with a 60°-120°F temperature range & positive off; 3 phase heaters have 3 pole thermostat for positive off position with a 60°-165° temperature range
- Manual reset thermal limit switch.
- ‡ &RUURVLRQ UHVLVWDQW VWHHO WXEXODU HOHPHQ
- Permanently lubricated, unit bearing, shaded pole motor with impedance protection.
- Propeller type fan blade: 1400 RPM motor; 245 CFM
- Factory installed options:
  - contactors (3420 & 3450 series)
  - circuit breakers (3450 series)
  - control transformers (3450 series)
- Made in U.S.A.

Note: Wall box required - may be ordered early for rough in purposes.

Standard Models

HEATER		WALL BOX		WATTS	BTUs	VOLTS	PH	AMPS	WT. (LBS)
MFG CATALOG NUMBER	MFG MODEL NUMBER	MFG CATALOG NUMBER	MFG MODEL NUMBER						
SERIES 3420 - ROUGH-IN DIMENSIONS: 19" H x 14 1/8" W x 4 1/8" D GRILL DIMENSIONS: 21 15/32" H x 17 7/16" W									
06911302	F3422T	06915702	Box 3420	2000	6826	208	1	9.6	41
06911902	H3422T					240		8.3	
06911702	G3422T					277		7.2	
03846202	J3422T			2000	6826	208	3	5.6	
03846402	K3422T					240		4.8	
06912302	F3423T			3000	10239	208	1	14.4	
06913102	H3423T					240		12.5	
06912702	G3423T					277		10.8	
03846302	J3423T			3000	10239	208	3	8.3	
03846502	K3423T					240		7.3	
06913302	F3424T			4000	13652	208	1	19.2	
06913802	H3424T					240		16.7	
06913602	G3424T					277		14.4	
06914002	J3424T					208	3	11.1	
06914102	K3424T					240		9.6	
06914302	F3425T			5000	17065	208	1	24	
06915102	H3425T					240		20.8	
06914802	G3425T					277		18.1	
06915302	J3425T					208	3	13.9	
06915602	K3425T					240		12.0	

HEATER		WALL BOX		WATTS	BTUs	VOLTS	PH	AMPS	WT. (LBS)
MFG CATALOG NUMBER	MFG MODEL NUMBER	MFG CATALOG NUMBER	MFG MODEL NUMBER						
SERIES 3450 - ROUGH-IN DIMENSIONS: 23" H x 14 1/8" W x 4 1/8" D GRILL DIMENSIONS: 25 1/32" H x 17 7/16" W									
06916102	F3452T	06919102	Box 3450	2000	6826	208	1	9.6	55
06916802	H3452T					240		8.3	
03122902	G3452T					277		7.2	
03846602	J3452T			2000	6826	208	3	5.6	
03846801	K3452T					240		4.8	
06876802	F3453T			3000	10239	208	1	14.4	
06917702	H3453T					240		12.5	
03122802	G3453T					277		10.8	
03846702	J3453T			3000	10239	208	3	8.3	
03846901	K3453T					240		7.3	
06917802	F3454T			4000	13652	208	1	19.2	
06918102	H3454T					240		16.7	
03119902	G3454T					277		14.4	
06918502	J3454T					208	3	11.1	
03166502	K3454T					240		9.6	
03129802	F3455T			5000	17065	208	1	24.03	
03121302	H3455T					240		20.8	
03123802	G3455T					277		18.1	
06919002	J3455T					208	3	13.9	
03130702	K3455T					240		12.0	