



Cable Puller: 8000 lb. (35.8kN) rated



Nothing Pulls Like The ULTRA Tugger™

- Pulls up to 8,000 lbs.
- Versi-Boom™ System allows you to make versatile and fast set-ups and pull 10' or 20' of extra cable easily.
- Uses standard 3" rigid steel conduit for boom.
- Direct gear drive.
- Lightweight.
- Portable.
- Optional deluxe force gauge.

Cat. No.	UPC No.	Description
6800	00985	Ultra Tugger™ Cable Puller with Standard Force Gauge, and Floor Mount.
6800-22	03196	Same as 6800 except 220 VAC 50 HZ.
6801	00986	Ultra Tugger™ Cable Puller with Standard Force Gauge, and Conduit Chain Mount.
6802	00987	Ultra Tugger™ Cable Puller with Standard Force Gauge, Pipe Adapter Sheave, Floor Mount, Versi-Boom™ System and "T" Stand without the Versi-Boom™ excludes Extensions and Elbow, Wheeled Carriage, Screw-on Couplers, or Rope.
6802-22	03197	Same as 6802 except 220 VAC 50 HZ.
6803	00991	Same as the 6802 plus 7/8" x 300' (22.2 mm x 91 m) Double-Braided Composite Rope.
6804	00992	Same as the 6802 plus 7/8" x 600' (22.2 mm x 182 m) Double-Braided Composite Rope.
6805	00993	Same as the 6802 plus the Versi-Boom™ Plus Extension and Elbow, Wheeled Carriage and 3", 3-1/2" and 4" Screw-on Couplers without Rope.
6805-22	03198	Same as 6805 except 220 VAC 50 HZ.

SPECIFICATIONS

Weight: 86 lbs. (39 kg)

Dimensions:

Length – 11.5 in. (292.1 mm), Width – 26 in. (660.4 mm), Height – 8.5 in. (215.9 mm)

Drive Motor: 1-1/2 Horsepower

Power Source 6800, 01, 02, 03, 04 and 05: 120 V 20 A

Power Source 6800-22, 02-22 and 05-22: 220 VAC 50 HZ

Pulling Force: Maximum – 8,000 lbs. (35.8 kN), Continuous – 6,500 lbs. (28.9 kN)

Pulling Speed - Feet (Meters) Per Minute: No Load: 9 fpm, At 2000 lbs. (8.8 kN): 8 fpm, At 4000 lbs. (17.9 kN): 7.5 fpm, At 6000 lbs. (26.7 kN): 7 fpm, At 8000 lbs (35.8 kN): 6 fpm

Power Source: 120 V 20 A

Rope – Average Breaking Strength or More: 7/8 diameter (22.2 mm); Double-Braided Polyester Composite – Rated at 32,000 lbs. (142 kN)



6800 / 00985
Floor Mount
Package



6801 / 00986
Conduit or Pole
Mount Package



6802 / 00987: Basic
Package without rope



6803 / 00991: Basic Pkg
with 300' rope



6804 / 00992: Basic Pkg
with 600' rope



6805 / 00993: Deluxe
Pkg with wheeled carriage
w/out rope

	Cat./UPC No.	Description	6800	6801	6802	6803	6804	6805
	08000	Ultra Tugger™	✓	✓	✓	✓	✓	✓
	01069	Force Gauge	✓	✓	✓	✓	✓	✓
	00862	Pipe Adapter Sheave			✓	✓	✓	✓
	00863	Elbow Unit				✓		✓
	00864	Nose Unit			✓	✓	✓	✓
	00865	Floor Mount	✓		✓	✓	✓	✓
	00866	Chain Mount		✓				
	00867	"T" Stand			✓	✓	✓	✓
	00870	Wheeled Carriage						✓
	00871	Boom Mount			✓	✓	✓	✓
	00835	3' Boom Tube						✓
	00791	4' Boom Tube			✓	✓	✓	✓
	00811	3" Slip-in Coupling			✓	✓	✓	✓
	00815	3-1/2" Slip-in Coupling			✓	✓	✓	✓
	00820	4" Slip-in Coupling			✓	✓	✓	✓
	00799	Adapter for Screw-on Coupling						✓
	00782	3" Screw-on Coupling						✓
	00783	3-1/2" Screw-on Coupling						✓
	00784	4" Screw-on Coupling						✓
	34136	7/8" x 300' (22.2 mm x 91 m) Rope				✓		
	34137	7/8" x 600' (22.2 mm x 182 m) Rope					✓	
	654/34362	Rope Stand				✓	✓	
	3048/23362	Storage Box			✓	✓	✓	✓
	603/23405	Castors - 2 Rigid, 2 Swivel			✓	✓	✓	✓