LITHONIA LIGHTING®

Catalog Number	
Notes	
Type	

FEATURES & SPECIFICATIONS

INTENDED USE — The OLCFM provides years of maintenance-free general illumination for residential and commercial outdoor applications such as porches, covered walkways and store entrances.

CONSTRUCTION — Rugged cast-aluminum top-plate and outer-ring are protected by a thermoset powder coat finish that provides superior resistance to corrosion and weathering. A tightly controlled multi-stage process ensures a minimum 3 mils thickness for a finish that can withstand extreme climate changes without cracking or peeling.

Polycarbonate LED lens/cover protects LEDs.

Fixture weight = 2.98 lbs.

OPTICS — 96 high-performance LEDs produces up to 1077 lumens and maintain 70% of light output at 50,000 hours of service.

(LED lifespan based on IESNA LM-80-08 results and calculated per IESNA TM-21-11 methodology.)

White acrylic diffuser provides a soft white light at 4000K CCT

See Lighting Facts Labels for specific fixture performance.

ELECTRICAL — Fixture operates at 120 volts, 60 Hz.

Standard input = 16.6 watts

Operating temperature -40ºC to 40ºC.

Amps @ 120V = .131.

Surge protection = 2.5kV.

INSTALLATION — Mounts easily to existing junction box (by others).

LISTINGS — UL Listed to U.S. and Canadian safety standards for wet locations.

Designed for ceiling or wall mounting more than 4' above the ground.

Tested in accordance with IESNA LM-79 and LM-80 standards.

WARRANTY — 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:
www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications subject to change without notice.



Outdoor General Purpose

OLCFM

OUTDOOR LED CAST FLUSH MOUNT


c UL us LISTED

LED

WET LOCATION™

5 YEAR warranty

All dimensions are inches (centimeters) unless otherwise indicated.



ORDERING INFORMATION All configurations of this product are considered "standard" and have short lead times.

Example: OLCFM 15 DDB


OLCFM				
Series	**Light Engine**	**Color Temperature (CCT)[1]**	**Voltage**	**Finish**
OLCFM	**15**	**(blank)** 4000K	**(blank)** 120V	DDB Dark bronze


Notes


1 Nominal Correlated Color Temperature (CCT) per ANSI C78.377-2008.


PHOTOMETRIC DIAGRAMS

To see complete photometric reports or download .ies files for this product,visit www.Lithonia.com. Tested in accordance with IESNA LM- 79 and LM- 80 standards.









 © 2013-2022 Acuity Brands Lighting, Inc. All rights reserved.