



Catalog No. TPL412C

Description: 125A 4CRT 1P3W 120/240V 22KIC COMBO

UPC No 783164191271

Home > Load Centers > Residential Load Centers

Panelboards No. 67 60 degree/75 degree centigrade Conductor Rating Suitable for use as service entrance equipment when Installed in accordance with the National Electrical Code 22kAIC RMS symmetrical, Except Where Noted 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down For a listing of CSA Listed load centers, visit www.geelectrical.com Amperage 125 A 412C1271

Descriptors

Category	Residential Load Centers
GO Schedule	RA
Grouping	Single Phase - USA

Specifications

Type	Standard
Interrupting Capacity Rating	10
Amperage	125 A
Device type	Main Lugs
Enclosure	Thermoplastic Enclosure,Indoor
Phase	1 Phase
Socket Type	0
1" Space	4
1/2" Space	8 2 4
Feed	Either
Door	No
GSA Compliance	Yes
Input/Output Voltage	120/240V ac

Classifications

UL/CUL Listing	UL
----------------	----

Publications

Title	Publication No.	Publication Type
PowerMark Gold* Load Centers, Q-Line Circuit Breakers and Accessories Guide	DET1023	Application and Technical
Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. Outdoor Load Center	10103091-SH35	Drawings-Outline and Dimensional
1 page outline drawing in pdf format.		

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.