

Eaton 170M3765

Catalog Number: 170M3765

Fuse-link, high speed, 200 A, AC 690 V, compact size 1, 45 x 59 x 148 mm, aR, IEC, UL, single indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M3765
	UPC
	051712257220
EAN	Product Length/Depth
5027590449953	92 mm
Product Height	Product Width
60 mm	163 mm
Product Weight	Warranty
176 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	UL Recognized IEC Rated



Product specifications

Interrupt rating

200 kAIC

Center-to-center distance of connections

117 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Amperage Rating

200 A

Fuse type

US Style

FKE/115 Type K indicator for micro

Fitted with:

Type K Indicator for micro

Fuse size

1

Voltage rating

690 V

Fuse indicator

Other

Construction size

1

Clearing (I2T)

15000 at 660 V

Rated voltage AC

690 V

Color

None

Connection

Blade end x blade end

Mounting dimension

M10

Utilization category

aR (accompanied semiconductor protection)

Resources

Catalogs

Product overview for machinery

Bussmann series complete full line catalog no. 1007

170M3765~Eaton Bussmann series high speed square body fuse

Compliance information

UKCA Fuse-links for the protection of semiconductor devices, sz1* up to 630A

CE Fuse-links for the protection of semiconductor devices, sz1* up to 630A

Specifications and datasheets

Eaton Specification Sheet - 170M3765

Watt losses

35 W

Type

Fuse

Fuse shape

Square body, center bolted tags

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

2200

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)