

**Kellems® Wire Management Products**  
**Strain Relief Grips**  
**Deluxe Cord Grips**

# HUBBELL

### Features

- Stainless Steel Fitting
- Stainless steel mesh is corrosion resistant
- Neoprene bushing is oil and watertight

### Ordering Information

Description	Form Size	UPC	Catalog Number
Stainless Steel Fittings and Mesh, Straight Male Thread	F4	783585334479	CG812SST

### Listings

UL Listed  
CSA Certified

### Specifications

Strand	Stainless Steel
Fittings	Stainless Steel
Bushings	Neoprene
NPT Thread Size	1 Inch

### Performance

<b>Environmental</b>	
Flammability	UL 94HB (Strand grip), UL 94V-2(Fitting)
Hazardous Locations	Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C
Operating Temperatures	-30°F to +240°F (-34°C to +115°C)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting



### Online Resources

eCatalog

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

