



Representative Image

## Catalog No. TM3215CCU

**Description: 150A 32CT 1P3W 120/240V 22K IC COMB**

**UPC No 783164112535**

**Home > Load Centers > Residential Load Centers**

Panelboards No. 67 60 degree/75 degree centigrade Conductor Rating Suitable for use as service entrance equipment when Installed in accordance with the National Electrical Code 22kAIC RMS symmetrical, Except Where Noted 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down For a listing of CSA Listed load centers, visit [www.geelectrical.com](http://www.geelectrical.com) Amperage 150 A 5CCU2535

### Descriptors

Category	Residential Load Centers
GO Schedule	RD
Grouping	Single Phase - USA

### Specifications

Type	Standard
Interrupting Capacity Rating	22
Amperage	150 A
Device type	Main Breaker
Enclosure	Indoor Type 1 Enclosure, Combination
Phase	1 Phase
1" Space	32
1/2" Space	0
Feed	Either
Door	Yes
GSA Compliance	Yes
Input/Output Voltage	120/240V ac

### Classifications

UL/CUL Listing	UL
----------------	----

## Publications

Title	Publication No.	Publication Type
<a href="#">PowerMark Gold* Load Centers, Q-Line Circuit Breakers and Accessories Guide</a> Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line. <a href="#">Indoor Load Center</a>	DET1023	Application and Technical
1 page outline drawing in pdf format.	10103091-SH21	Drawings-Outline and Dimensional

**Additional Documentation:** Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.