Search Results

Evaluate
- Brochures
  - PDF-TX6 10Gig UT ..
- FAQ's
- Press Releases
  - COM/ABOUTUS/PRESSROOM/PRESSRELEASES/106347-PANDUIT Veri ..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips Within Results

☒ **Text Search: 'UTP6X3 '**

Your search criteria matched only one product, shown below

UTP6X3Y



• Exceed draft requirements of TIA/EIA-568-B.2-AD10 and ISO 11801 Class E_A Edition 2.1 and IEEE 802.3an-2006 ratified standard channel requirements for supporting 10GBASE-T
• Each patch cord is 100% performance tested and wired T568B
• Constructed of *TX6™ 10Gig™* 24 AWG solid copper cable (nominal cable diameter is .275 inches) and *TX6™ PLUS* Modular Plugs for superior performance
• Plug meets all applicable FCC part 68 Subpart F requirements and exceeds IEC 60603-7 specifications
• Slender strain relief boot provides easy access in high density applications
• Plug uses an integral pair manager to optimize performance and consistency by reducing untwisting of conductors within the plug
• Plug performance in center of TIA/EIA component range, ensuring interoperability and 10GBASE-T Ethernet channel performance
• Labels on patch cords provide identification of performance level, length, and quality control number
• Patented tangle free latch prevents snags and provides easy release, saving time on frequent moves, adds, and changes

Part Number	UTP6X3Y
RoHS Compliancy Status	Compliant
Note	UTP6X3Y replaces UTP6X3
Part Description	Category 6A, 10Gb/s UTP patch cord with TX6™ PLUS Modular Plugs on each end.
Product Type	Copper Patch Cord
Color	Off White
Length (ft.)	3
Length (m)	0.91
Boot Color	Clear
Cable Color	Off White
Cable Type	UTP
Flammability Rating	CM